

HUNAN HUAWEI SOLAR CO., LTD

Mono 125X125 mm Monocrystalline Silicon Solar Cells

Dimension(mm): 125 X125(± 0.5)

Diagonal(mm): 165 ± 0.1

Thickness(μ m): 200 ± 20

Front(-): 1.5mm busbar(Ag),silicon nitride

Back(+):3.5 mm busbar(Ag/Al),closed aluminium BSF



Dimension (mm)	Coverision efficiency(%)	Maximun power Pmax(W)	Optimun operating voltage (V)	Optimun operating current (A)	Open circuit voltage (V)	Short circuit current (A)
125X125.Φ165	17.80-18.00	2.76	0.528	5.223	0.63	5.58
125X125.Φ165	17.60-17.80	2.73	0.526	5.191	0.629	5.558
125X125.Φ165	17.40-17.60	2.7	0.524	5.158	0.628	5.534
125X125.Φ165	17.20-17.40	2.66	0.52	5.12	0.627	5.503
125X125.Φ165	17.00-17.20	2.63	0.518	5.076	0.626	5.462
125X125.Φ165	16.80-17.00	2.6	0.517	5.032	0.625	5.41
125X125.Φ165	16.60-16.80	2.57	0.516	4.981	0.624	5.375
125X125.Φ165	16.30-16.60	2.55	0.516	4.944	0.623	5.336
125X125.Φ165	15.90-16.30	2.49	0.507	4.909	0.62	5.291
125X125.Φ165	15.50-15.90	2.43	0.501	4.855	0.611	5.246

Add: Linyin Road,Economical Development Zone,Phoenix Garden,Yongzhou,Hunan,China

Web: www.huaweisolar.com Tel: +86-746-8226998 Fax: +86-746-8226186