



**Dunya Prestige Electric  
Electronics, Defense Co., Ltd.**

## **DPESOLAR 10A - CHARGE REGULATOR**

Voltage: 12V/12V DC (Automatic selection)
Max. Charge Current: 10A
Float Charge: 14.1 / 28.2V
Boost Charge: 14.4 / 28.8V
Battery Low Voltage Cut off: 11.1 /22.2V
Reconnect Voltage: 12.6 / 25.2V
Max self consumption : 12 mA
Warranty :2 years
Ambient Temperature : -10 °C... +50 °C
<b>Charging Regulation Five Stages:</b> Bulk, Absorption, Float, Silent and Equalization
LED in symbols and digits showing.
Reverse Polarization Protection
<b>Night-Light Function</b>
Short circuit of Solar and Load Protection
Over Voltage Protection
Over Temperature Protection
Anti bounce-charge control
Over current protection
Auto control of SOC discharge process of storage battery
Terminal (Fine/single wire) 10mm <sup>2</sup>

**Keresteciler Sitesi C Blok 231.Sokak No: 24 Ostim/Macunkoy Ankara/Turkey**

▪ Tel: +90 312 354 92 27(PBX) ▪ Fax: +90 312 354 92 28 ▪ Mail:info@dpesolar.com

