



### PWM CHARGE CONTROLLER

Model NO.	Picture	Features	Rated Voltage	Max Charge/ Discharge Current
CMTD-A2410		<ol style="list-style-type: none"> <li>1. Visible LCD display</li> <li>2. With temperature compensation</li> <li>3. Full protection</li> <li>4. Protection from reverse polarity</li> <li>5. USB output 5V/2A*2</li> <li>6. 12V/24V auto detect</li> <li>7. Protection of reversed polarity</li> <li>8. CE passed</li> </ol>	12V/24V	10A
CMTD-A2420			12V/24V AUTO DETECT	20A
CMTD-A2430			12V/24V AUTO DETECT	30A

1. Max. Solar Panel Input Voltage:  $\leq 50V$  DC
2. Stop Charge Voltage: 14.7V/29.4V DC
3. Low Voltage Recoverage: 12.2V/24.4V DC
4. Low Voltage Protection: 10.5V/21.0V DC
5. USB Output Voltage/Current: 5V 2A
6. Loss when No load:  $\leq 10mA$
7. Temperature Compensation:  $-3mV/cell/^{\circ}C$
8. Operation Temperature:  $-20^{\circ}C$  to  $60^{\circ}C$
9. Protection: Over temprature, low voltage, reverse polarity, overload, short circuit

Payment Terms: T/T (30% deposit, 70% balance before shipping)

Lead Time: 7 days after received deposit & Order details confirmed.