



## SPECIFICATION OF 240W,250W POLY SOLAR MODULE

### Poly-Crystalline

Module type	Pm(W)	Number of cell	Cell Dimension (mm)	Max System Voltage(V)	Vm(V)	Im(A)	Voc(V)	Isc(A)
TYSM240	240W	72	156	1000	35	6.86	43.05	7.34
TYSM250	250W	72	156	1000	35	7.14	43.05	7.64

### Parameter

Maximum system voltage (V)	1000
Temperature coefficients of Isc (%)	+0.1%/°C
Temperature coefficients of Voc (%)	-0.38%/°C
Temperature coefficients of Pm (%)	-0.47%/°C
Temperature coefficients of Im (%)	+0.1%/°C
Temperature coefficients of Vm (%)	-0.38%/°C
Temperature Range	-40°C ---85°C
Tolerance Wattage (e.g. +/-5%)	± 5%
Surface Maximum Load Capacity	60m/s (200kg/sq.m)
Junction Box Type	PPO, black
Connectors and Cables Type	4mm <sup>2</sup>
Length of Cables (mm)	900
Cell Efficiency (%)	>16.0%
Output tolerance (%)	± 5%
Frame (Material, Corners, etc.)	Anodized Aluminum Alloy
Standard Test Conditions	AM1.5 100MW/cm <sup>2</sup> 25°C
Guarantee of power	5 years for whole products,90% power for 10years, 80% power for 25years.
FF (%)	≥73.3%



### Physical Characters

Output	Module Net Weight	Module Size (MM)	Packing	20' Container	40' Container
240W	19.0(kg)	990*1955*45	2pcs/carton	192 pcs	384 pcs
250W	19.0(kg)	990*1955*45	2pcs/carton	192 pcs	384 pcs

深圳市拓阳新能源科技有限公司  
 SHENZHEN TUOYANG NEW ENERGY CO., LTD  
 Tel: +86-755-2305 5561 Mobile : +86-13717084860  
 www.sztuoyang.com Email:szsyty@163.com

