

Monocrystalline Solar Panel Specifications

Peak Power (Pmax)	Voltage at Pmax (V)	Current at Pmax (A)	Open Circuit Voltage (V)	Short Circuit Current (A)	Dimension (MM)	Weight (KG)
5watt	18.6	0.27	22.5	0.29	250x185x18	0.6
10watt	18.6	0.54	22.5	0.59	345x265x18	1.05
15watt	18.6	0.81	22.5	0.87	355x350x18	1.5
20watt	18.6	1.08	22.5	1.18	450x350x18	1.85
25watt	18.6	1.34	22.5	1.46	540x350x25	2.27
30watt	18.6	1.61	22.5	1.74	635x350x25	2.67
40watt	18.6	2.15	22.5	2.33	670x445x25	3.36
45watt	18.6	2.42	22.5	2.64	670x495x25	3.73
50watt	18.6	2.69	22.5	2.92	670x540x30	4.07
60watt	18.6	3.23	22.5	3.51	670x630x30	4.75
70watt	18.6	3.76	22.5	4.10	725x670x30	5.5
75watt	18.6	4.03	22.5	4.38	770x670x30	5.8
80watt	18.6	4.3	22.5	4.66	815x670x30	6.2
90watt	18.6	4.84	22.5	5.25	910x670x30	6.9
100watt	18.6	5.38	22.5	5.84	1010x670x30	7.6
110watt	18.6	5.91	22.5	6.43	1100x670x30	8.3
120watt	18.6	6.45	22.5	7.02	1200x670x35	9.1
130watt	18.6	6.99	22.5	7.58	1290x670x35	10.1
140watt	18.6	7.53	22.5	8.17	1380x670x35	10.8
150watt	18.6	8.06	22.5	8.54	1480x670x35	12.0
220watt	27.7	7.94	33.6	8.5	1480x990x35	16.7
230watt	28.2	8.16	34	8.61	1480x990x35	16.7
250watt	31.1	8.04	37.6	8.56	1640x990x45	19.6
260watt	31.6	8.23	37.9	8.67	1640x990x45	19.6
290watt	37	7.84	44.8	8.5	1956x990x50	23.1
300watt	37.4	8.02	45.2	8.61	1956x992x50	23.1
305watt	37.6	8.11	45.4	8.64	1956x992x50	23.1
310watt	37.8	8.20	45.5	8.67	1956x992x50	23.1

WASONLONG Solar Technology Co., Ltd.

4F, No. 13, Chuangye Yi Road, Longgang District, Shenzhen, China

Tel: (86) 755 85224431

Fax: (86) 755 89628023

www.wsl-solar.com

info@wsl-solar.com