

Module 组件	TDM105P-B-24		
Series 串联	3BB-PB-24		
Encapsulation 封装	Glass/EVA/Cell/EVA/TPT 玻璃/EVA/电池片/EVA/背板		
Size and Number of cells 电池片尺寸和数量	156mm*156mm 24/12*2pcs 156 毫米*156 毫米 24/12*2pcs		
Pmax 最大功率(W)	105	100	95
Module Efficiency 组件效率(%)	15.08	14.36	13.64
Tolerance 公差	+3%		
Voc 开路电压(V)	15.90	15.46	15.25
Isc 短路电流(A)	8.62	8.47	8.26
Vmp 最大功率电压(V)	12.72	12.47	11.94
Imp 最大功率电流(A)	8.26	8.02	7.96
Max. Syst. Open Voltage 最大系统开路电压(V)	1000		
Diodes 二极管	3by-pass		
Dimension 尺寸(mm)	1956×356×50 1956×356×40 1956×356×35		
Weight 重量(kg)	12/11/10		
MAX Over Current Protecng Rating 最大过电流保护率(A)	15		
Operate Temp Scope 操作温度范围℃	-40~+85		
Relative humidity 相对湿度%	0~100%		
Frame Thickness 边框厚度	Quantity 数量/Container 集装箱		
50mm	720pcs/20GP	1584pcs/40HQ	
Cell Technology 电池片技术	multi-Si		

Output

Cable	4.0mm ² (TUV)	Length	950mm	Connector	MC Type
-------	--------------------------	--------	-------	-----------	---------

