



SUNTIME ENERGY

C-123, ELTOP Industrial Area, Phase 8, Mohali, Punjab

Phone No: 01725094898

Email: info@suntimenergy.com

Nominal Power Output (W)	20	37	40	50	75	100	150	250
Voltage at Pmax (V)	17.08	17.17	17.18	17.21	17.34	17.46	17.72	30
Current at Pmax (A)	1.18	2.16	2.33	2.91	4.33	5.73	8.47	8.35
Open-Circuit Voltage Voc (V)	21.17	21.34	21.37	21.47	21.72	21.97	22.47	37
Short-Circuit Current Isc (A)	1.26	2.31	2.50	3.11	4.60	6.07	8.90	8.95
Maximum System Voltage	600	600	1000	1000	1000	1000	1000	1000
Module Dimensions (mm)	460 x 350 x 22	485 x 675 x 30	520 x 675 x 35	630 x 675 x 35	900 x 675 x 35	1150 x 675 x 35	1490 x 675 x 35	1640 x 992 x 40
Module Weight	1.95	4.25	4.80	5.15	7.95	10.15	13	18.5
Number of Cells	36	36	36	36	36	36	36	60
Frame Material	Anodised Aluminium							
	STC : Irradiance 1000W/m ² , Module Temperature 25 C, Spectrum AM 1.5							
	Guaranteed Power Output of 90% for 10 Years and 80% for 25 Years							