


JST MODULE

- JST80P(18) 80W
- JST85P(18) 85W
- JST90P(18) 90W
- JST95P(18) 95W
- JST100P(18) 100W
- JST105P(18) 105W



High conversion efficiency
High module efficiency to guarantee power output.



0 to +5W positive tolerance
Detailed information in Electrical Specifications.




Self-cleaning glass
Coating glass for self-cleaning, reduce surface dust.



48-hour response service



Outstanding low irradiation performance
Excellent module efficiency even in the weak light conditions, such as morning or cloudy.



Excellent loading capability
2400Pa wind loads, 5400Pa snow loads.



25-year performance warranty



10-year warranty on materials and workmanship

IEC 61215 Ed.2
IEC 61730
UL 1703



ELECTRICAL DATA

Model Type	JST80P(18)	JST85P(18)	JST90P(18)	JST95P(18)	JST100P(18)	JST105P(18)
Peak Power (Pmax)	80W	85W	90W	95W	100W	105W
Module Efficiency	15.18%	16.13%	17.08%	18.03%	18.98%	19.93%
Maximum Power Voltage (Vmp)	9.4V	9.5V	9.6V	9.6V	9.7V	9.8V
Maximum Power Current (Imp)	8.48A	8.94A	9.40A	9.85A	10.29A	10.72A
Open Circuit Voltage (Voc)	11.4V	11.4V	11.5V	11.6V	11.7V	11.7V
Short Circuit Current (Isc)	9.52A	9.98A	10.43A	10.86A	11.28A	11.69A
Power Tolerance				±3%		
Maximum System Voltage				1000V		
Nominal Operating Cell Temperature				44.4±2°C		
Maximum Series Fuse Rating				15A		

MECHANICAL DATA

Cell Type	156×156mm
Number of Cells	18 (3×6)
Weight	6.4kg
Dimension	531×992×50mm
Max Load	5400 Pascals
Junction Box	IP67 rated MC4
Connector	Compatible PV
Wire Type	Wire


TEMPERATURE CHARACTERISTICS

Temp. Coeff. of Isc (TK Isc)	0.04% /°C
Temp. Coeff. of Voc (TK Voc)	-0.34% /°C
Temp. Coeff. of Pmax (TK Pmax)	-0.44% /°C

PACKING MANNER


Container	20' GP	40' GP
Pieces per Pallet	26	26
Pieces per Container	600	1200

PHYSICAL CHARACTERISTICS




ELECTRICAL CHARACTERISTICS


Current-Voltage & Power-Voltage Curve (AM1.5, Cell Temperature 25°C)



Temperature Dependence of Isc, Voc and Pmax



Irradiance Dependence of Isc, Voc and Pmax (Cell Temperature: 25°C)



Note: the specifications are obtained under the Standard Test Conditions (STCs): 1000W/m² solar irradiance, 1.5 Air Mass, and cell temperature of 25°C. The NOCT is obtained under the Test Conditions: 800W/m², 20°C ambient temperature, 1m/s wind speed, AM 1.5 spectrum.
Please contact support@jusolar.com for technical support. The actual transactions will be subject to the contracts. This parameters is for reference only and it is not a part of the contracts. The specifications are subject to change without prior notice.