ADITYA SERIES MONO

WSM-255 to WSM-300 (60 Cells)



Superior Module Efficiency as per International Benchmarks

Positive Power Tolerance 0/+ 5W

PID Resistant Modules

Glass with Anti Reflective Coating Improves light transmission Salt mist, Ammonia and Hail Resistant

Sustain Heavy Wind & Snow loads (2400 Pa & 7500 Pa)


IP 67 rated MC4 compatible connectors

Excellent Performance in low light






I-V Curve Variation With Irradiance



I-V Curve Variation With Temperature



 The specifications are for reference purpose only. Waaree reserves the right to change the specifications without prior notice.

- INTERNATIONAL & NATIONAL CERTIFICATIONS -



















ADITYA SERIES MONO


WSM-255 to WSM-300 (60 Cells)



ELECTRICAL CHARACTERISTICS

MODELS	Pmax (W)	Vmp (V)	Imp (A)	Isc (A)	Voc (V)	Module Eff. (%)
WSM-255	255	30.00	8.50	9.00	36.50	15.71
WSM-260	260	30.25	8.60	9.15	36.60	16.02
WSM-265	265	30.50	8.70	9.30	36.70	16.34
WSM-270	270	30.90	8.75	9.40	37.20	16.65
WSM-275	275	31.10	8.85	9.55	37.40	16.95
WSM-280	280	31.40	8.93	9.65	37.60	17.27
WSM-285	285	31.50	9.05	9.75	37.90	17.56
WSM-290	290	31.60	9.20	9.80	38.20	17.91
WSM-295	295	31.80	9.28	9.85	38.50	18.18
WSM-300	300	32.00	9.38	9.95	38.80	18.49

DESIGN SPECIFICATIONS



MECHANICAL CHARACTERISTICS

Length x Width x Thickness (L x W x T) - mm	1640 x 990 x 40		
Mounting Holes Pitch (Y) – mm	1000.00		
Mounting Holes Pitch (X) – mm	942		
Weight (kg)	18.5		
Solar Cells per Module (Units) / Arrangement	60 / (10 x 6)		
Solar Cell Type	Mono crystalline Silicon		
Front Cover (Material / Thickness)	Tempered & Low Iron Glass / 3.2 mm		
Encapsulate	Ethylene Vinyl Acetate		
Frame Material	Anodized Aluminum Alloy		
Junction Box (Protection degree / Material)	Weatherproof PPO / IP67 rated		
	enclosure with bypass diodes		
Connector	IP67 rated / MC4 compatible		
Cable	4 mm ² cross section		
Fire safety class	С		
Safety application class	A		
Safety class	II		

THERMAL CHARACTERISTICS

Temperature coefficient of Current	0.0118
Temperature coefficient of Voltage	-0.2627
Temperature coefficient of Power	-0.3677
NOCT	46 <u>+</u> 2
Operating Temperature Range	-40 to 85

Waaree Energies Ltd. is the flagship company of Waaree Group, and has the country's largest Solar PV Module manufacturing capacity of 1.2 GW. In addition, it is one of leading players in India in EPC services, project development, rooftop solutions, solar water pumps, and as an Independent Power Producer. Waaree has its presence in over 250+ locations nationally and 68 countries globally.