



**30** YEAR LINEAR POWER WARRANTY  
 ANNI GARANZIA LINEARE PRODUZIONE

**20** YEAR PRODUCT WARRANTY  
 ANNI GARANZIA PRODOTTO

## COMMERCIAL LINE

**SG325P**

 "MADE IN ITALY" MODULE

PEIMAR polycrystalline solar panels made in Italy provide customers with a perfect combination of high-efficiency and versatility. Thanks to the use of high-quality solar cells, our panels achieve outstanding performance and ensure maximum production output even under poor lighting and weather conditions. The strong yet ultra-light frames, make installation easy but robust in either residential, commercial or large-scale settings.



**POSITIVE POWER OUTPUT TOLERANCE**



**PID FREE**



**MODULE FIRE PERFORMANCE: CLASS I**



**ANTI-REFLECTIVE GLASS**



**HAILSTORM RESISTANCE**

### CELLS

**72**  
POLY



**QTY:**  
72 CELLS  
**TYPE:**  
POLY 5BB  
**DIMENSION:**  
156x156 mm / 6x6"

### FRAME



### BACKSHEET



### JUNCTION BOX



**ELECTRICAL CHARACTERISTICS (STC)\***

	<b>SG325P</b>
Nominal Output (Pmax)	325 W
Flash Test Power Tolerance	0/+5 W
Voltage at Pmax (Vmp)	36.3 V
Current at Pmax (Imp)	8.96 A
Open Circuit Voltage (Voc)	44.6 V
Short Circuit Current (Isc)	9.74 A
Maximum System Voltage	1500 V
Maximum Series Fuse Rating	15 A
Module Efficiency	16.74%

**MECHANICAL CHARACTERISTICS**

Solar Cells	72 (6x12) polycrystalline
Solar Cells Size	156x156 mm / 6x6"
Front Cover	3.2 mm / 0.12" thick, low iron tempered glass
Back Cover	TPT (Tedlar-PET-Tedlar)
Encapsulant	EVA (Ethylene vinyl acetate)
Frame	Anodized aluminium alloy, double wall
Frame finishing	Silver
Backsheet finishing	White
Diodes	3 Bypass diodes serviceable
Junction Box	IP67 rated
Connector	MC4 or compatible connector
Cables Length	900 mm / 35.4"
Cables Section	4.0 mm <sup>2</sup> / 0.006 in <sup>2</sup>
Dimensions	1957x992x40 mm / 77x39x1.57"
Weight	22.5 Kg / 49.6 lbs
Max. Load	Certified to 5400 Pa

**TEMPERATURE CHARACTERISTICS**

NOCT**	45±2 °C
Temperature Coefficient of Pmax	-0.43 %/°C
Temperature Coefficient of Voc	-0.32 %/°C
Temperature Coefficient of Isc	0.047 %/°C
Operating Temperature	-40 °C ~ +85°C


**PACKAGING\*\*\***

Pallet dimensions	2000x1200x1200 mm / 79x47x47"
Pieces per pallet	27
Weight	622 Kg / 1371 lbs

**CERTIFICATIONS**


Fire Resistance Rating	1 (UNI 9177)
PID free	IEC TS 62804-1:2015

**DIMENSIONS**



**CURRENT/VOLTAGE CHARACTERISTICS**

Values apply to modules: SG325P



\*STC: (Standard Test Condition) Irradiance 1000W/m<sup>2</sup>; Module Temperature 25°C; Air Mass 1.5

\*\*NOCT: (Nominal Operation Cell Temperature) Sun 800W/m<sup>2</sup>; Air 20°C; Wind speed 1m/s

\*\*\*Pallets can be stacked up to two

It is important to point out, that all technical specifications, information and figures contained in this datasheet are estimated values. Peimar reserves the right to change the technical specifications, information and figures contained in this document at any time without notice.

WW\_VERS 1\_08/2018