



280 - 300 Wp

www.axitecsolar.com

AXITEC
high quality german solar brand

AXIprotect MT


60 cell glass/glass monocrystalline
High performance solar module

The advantages:

- 15** Years 15 years manufacturer's warranty
- PID free** PID-free through glass/glass-technology
- + Wp** Guaranteed positive power tolerance from 0-5 Wp by individual measurement
- 5.400 Pa** Maximum 5400 Pa snow load
- 100%** 100% electroluminescence inspection
- Soft Grip** High stability due to AXITEC-Soft-Grip-Seam aluminium frame construction
- IP 68** High quality junction box and connector systems

Exclusive linear AXITEC high performance guarantee!

- 15 years manufacturer's guarantee on 90% of the nominal performance
- 30 years manufacturer's guarantee on 82,5% of the nominal performance



AXIprotect MT 280 - 300 Wp

Electrical data (at standard conditions (STC) irradiance 1000 watt/m², spectrum AM 1,5 at a cell temperature of 25°C)

Type	Nominal output P _{mpp}	Nominal voltage U _{mpp}	Nominal current I _{mpp}	Short circuit current I _{sc}	Open circuit voltage U _{oc}	Module conversion efficiency
AC-280MG/60S	280 Wp	31,68 V	8,84 A	9,36 A	39,05 V	16,81 %
AC-285MG/60S	285 Wp	31,81 V	8,96 A	9,43 A	39,24 V	17,11 %
AC-290MG/60S	290 Wp	32,01 V	9,06 A	9,54 A	39,42 V	17,41 %
AC-295MG/60S	295 Wp	32,25 V	9,15 A	9,67 A	39,56 V	17,71 %
AC-300MG/60S	300 Wp	32,37 V	9,27 A	9,74 A	39,72 V	18,01 %

Design


Frontside	2 x 2,5 mm hardened, low-reflection white glass
Cells	60 monocrystalline high efficiency cells 156,75 mm x 156,75 mm (6")
Backside	Composite film (transparent)
Frame	35 mm silver anodized aluminium frame

Mechanical data

L x W x H	1666 x 1000 x 35 mm
Weight	22,5 kg with frame

Power connection

Socket	Protection Class IP68
Wire	approx. 1,2 m, 4 mm ²
Plug-in system	Plug/socket IP68



All dimensions in mm

Limit values

System voltage	1000 VDC
NOCT (nominal operating cell temperature)*	45°C +/-2K
Max. load-carrying capacity	5400 N/m ²
Reverse current feed IR	20,0 A
Permissible operating temperature	-40°C to 85°C / -40F to 185F

(No external voltages greater than U_{oc} may be applied to the module)

* NOCT, irradiance 800 W/m²; AM 1,5; wind speed 1 m/s; Temperature 20°C

Temperature coefficients

Voltage U _{oc}	-0,29 %/K
Current I _{sc}	0,04 %/K
Output P _{mpp}	-0,39 %/K

Low-light performance

 (Example for AC-300MG/60S)

I-U characteristic curve	Current I _{pp}	Voltage U _{pp}
200 W/m ²	2,15 A	30,17 V
400 W/m ²	3,71 A	31,20 V
600 W/m ²	6,05 A	31,81 V
800 W/m ²	7,57 A	32,10 V
1000 W/m ²	9,27 A	32,37 V

Packaging

Module pieces per pallet	30
Module pieces per HC-container	780