

Einnova Solarline

invented for solar




Mono crystalline Solar Module

Black ESM 360/365/370

FEATURES

- Excellent module efficiency up to 19.1% by using high efficient Monocrystalline solar cells 156x156mm
- Outstanding performance at low irradiance above 96.3%
- Heavy snow load up to 5400 Pa and wind load up to 3800Pa
- IP65 or 67 junction box is available for long term weather endurance
- Salt mist, ammonia and blowing sand resistance, apply to seaside, farm and desert areas
- Positive power tolerance up to 5w
- Selective materials and rigid process effectively control Potential Induced Degradation (PID)
- Total quality control and complete traceability of Material by Shop Floor Control (SFC)



WARRANTY

- 12 Years Product Workmanship Warranty
- 12 Years Minimum 90% Power Output
- 25 Years Minimum 80% Power Output

China Jiangsu
International Group Ltd.

5 West Beijing Road,
Nanjing, 210008, China

+86-(0)25-84792033
+86-(0)25-84705923

info@einnova-solarline.com
www.einnova-solarline.com


EN

The specifications are subject to change without prior notice.

Mono crystalline Solar Module

Black ESM 360/365/370

Einnova Solarline
invented for solar



Electrical Specification

Model Type	Unit	ESM 360	ESM 365	ESM 370
Maximum Power (Pmax)	W	360	320	370
Module Efficiency	%	18.6	18.8	19.1
Open Circuit Voltage (Voc)	V	47.5	47.8	48.2
Short Circuit Current (Isc)	A	9.71	9.75	9.80
Maximum Power Voltage (Vmp)	V	39.0	39.3	39.6
Maximum Power Current (Imp)	A	9.24	9.29	9.35
Maximum System Voltage	V	1000 (TUV) / 600 (UL)		
Maximum Series Fuse Rating	A	15		
Power Tolerance		0~+5W		

Standard Test Conditions (STC) of irradiance of 1000 W/m², spectrum AM 1.5 and cell temperature of 25°C.

The NOCT is obtained under the Test Conditions: 800W/m², 20°C ambient temperature, AM 1.5 Spectrum, 1m/s wind speed.

Mechanical Specification

Module Dimension (mm)	1956x 992x 40
Cell Dimension (mm)	156 x 156
Number of Cell	72 (6 x 12)
Glass Thickness (mm)	3.2
Weight (kgs)	21.0
Maximum Load (TUV) (Pascal)	5400
Junction Box and Cable connector	IP65 or IP 67 rated; MC4 compatible

Temperature Characteristics

Nominal Operating Cell Temperature (NOCT)	45 +/- 2 °C
Temperature Coefficient (Pmax)	-0.39% / °C
Temperature Coefficient (Voc)	-0.30% / °C
Temperature Coefficient (Isc)	0.05% / °C
Operating Temperature	-40~85 °C

IV CURVE

