




MANAGEMENT SYSTEM

-  ISO 9001: Quality management system
-  ISO 14001: Standard for environmental management system
-  OHSAS 18001: International standard for occupational health and safety assessment system



*BLACK FRAME/BLACK BACK-SHEET PRODUCTS ARE AVAILABLE UPON REQUEST

PRODUCT CERTIFICATES



Electrical Characteristics under STC*

Module Type	FSM140P636	FSM145P636	FSM150P636	FSM155P636	FSM160P636	FSM165P636
Maximum Power-Pmax (Wp)	140	145	150	155	160	165
Voltage at Maximum Power-Vmp (V)	18.2	18.3	18.4	18.5	18.6	18.8
Current at Maximum Power-Imp (A)	7.69	7.92	8.15	8.38	8.60	8.78
Open Circuit Voltage-Voc (V)	22.2	22.3	22.4	22.5	22.6	22.9
Short Circuit Voltage-Isc (A)	8.31	8.56	8.80	9.05	9.27	9.46
Module Efficiency- η_m (%)	14.2	14.7	15.2	15.7	16.2	16.7
Power Tolerance (%)	0/+3	0/+3	0/+3	0/+3	0/+3	±3

*STC (Standard Testing Conditions): Irradiance 1000W/m², cell temperature 25°C, AM=1.5

*NOCT (Nominal Operating Cell Temperature): Irradiance 800W/m², ambient temperature 20°C, wind speed 1 m/s

Mechanical Characteristics

Cell Type	Poly-crystalline 156.75×156.75mm
Number of Cells	36 (4×9)
Dimension	1488×664×30mm
Weight	12 kg

Temperature Characteristics

NOCT*	45±2°C
Temperature Coefficient of Pmax (%)	-0.40/°C
Temperature Coefficient of Voc (%)	-0.31/°C
Temperature Coefficient of Isc (%)	0.04/°C

Maximum System Ratings

Operating Temperature	-40°C to +85°C
Maximum System Voltage	1000V DC
Maximum Series Fuse Rating	16A

Packing Configuration

Quantity per Cartoon	35 pieces
Quantity per 20' Container	490 pieces
Quantity per 40' Container	1,470 pieces

* The datasheet is for informational purposes only and subject to change without prior notice. Copyright © 2018 TAMRONS All rights reserved.



Positive Power Tolerance +0 ~ +4.99 w



Withstand Heavy Loading
Front load 5400 Pa & Rear Load 2400 Pa



Excellent Low Light Performance
3.5% relative eff. reduction at low-irradiance (200w/m²)



Tamrons Active International Limited

web: www.tamrons.com; mail: sales@tamrons.com

Production plants in China, Taiwan, Dubai and Thailand

can meet the customer's needs and brand OEM

