

# SOLAR MODULE

## EGE-180/190P-72-36V

### POLYCRYSTALLINE MODULE

180-190 W / 72 Cells / 5 Bus bars



Eco Green Energy's modules are only made of grade A solar cells with a very high efficiency and ensured more than 25 years lifespan.


#### KEY FEATURES




5 bus bars cells, with efficiency up to 19 %



IP65 or IP67 junction box for long term weather endurance



High quality aluminum frame, resisting load up to 5400 Pa and wind pressure up to 2400 Pa



High transmissivity, low-iron tempered glass



High performance in low-light environment



Double EL test before and after lamination



**OUTPUT POWER WARRANTY**





**PRODUCT WARRANTY**

#### CERTIFICATES

IEC 61215 / IEC 61730 / CE  
ISO 9001:2015

#### LINEAR PERFORMANCE WARRANTY

10-Year Product Warranty · 25-Year Linear Power Warranty



## ELECTRICAL DATA AT STC\*

Power output (Pmax)	180 W	185 W	190 W
Power tolerance	0~+5 W	0~+5 W	0~+5 W
Module efficiency	15.12 %	15.54 %	15.96 %
Maximum power voltage (Vmp)	36.00 V	36.10 V	36.25 V
Maximum power current (Imp)	5.00 A	5.12 A	5.24 A
Open circuit voltage (Voc)	44.89 V	44.98 V	45.13 V
Short circuit current (Isc)	5.31 A	5.44 A	5.55 A

\*Standard Test Conditions: Irradiance: 1 000 W / m<sup>2</sup> • Cell temperature: 25°C • AM: 1.5

## ELECTRICAL DATA AT NOCT\*

Power output (Pmax)	133.16 W	136.86 W	140.56 W
Maximum power voltage (Vmp)	33.25 V	33.34 V	33.48 V
Maximum power current (Imp)	4.00 A	4.10 A	4.19 A
Open circuit voltage (Voc)	41.67 V	41.75 V	41.89 V
Short circuit current (Isc)	4.31 A	4.42 A	4.51 A

\*Nominal Operating Cell Temperature: Irradiance: 800 W / m<sup>2</sup> • Ambient temperature: 20°C • AM: 1.5 • Wind speed: 1 m/s

## TEMPERATURE CHARACTERISTICS

NOCT	45 °C ±2 °C
Temperature coefficient of Pmax	-0.41%/°C
Temperature coefficient of Voc	-0.31%/°C
Temperature coefficient of Isc	+0.06%/°C

## MAXIMUM RATINGS

Operating temperature range	-45 °C ~+85 °C
Maximum system voltage	1500 V
Max series fuse rating	10 A
Max front load (e.g.: snow)	5 400 Pa
Max back load (e.g.: wind)	2 400 Pa


## MECHANICAL CHARACTERISTICS

Cell type	Polycrystalline (156x93 mm)
Number of cells	72
Dimensions	1200x992x35 mm
Weight	13.7 kg
Glass	3.2 mm tempered glass
Frame	Anodized aluminium alloy
Junction box	IP65 or IP67
Cable	0.9 m
Connector	MC4 or MC4 compatible

## EMBALAJE

Type	Pcs	Weight
Pallet	35 pcs	410 kg
20ft GP Container	720 pcs	8.4 t
40ft GP Container	1400 pcs	16.6 t
40ft HQ Container	1800 pcs	21.2 t

## I-V CURVES



## ENGINEERING DRAWINGS (mm)

