

PANDA BIFACIAL 144HCL




20.5%
CELL EFFICIENCY

10 YEAR
PRODUCT WARRANTY

0-5W
POWER TOLERANCE

PANDA BIFACIAL 30 Years Linear Warranty



DUAL POWER MAXIMIZED YIELD

PANDA BIFACIAL modules generate power from the front as well as from the back side. Together with the cutting-edge PANDA N-type crystalline silicon solar cells, which wake up earlier than conventional P-type and go to sleep later, the energy yield can be increased by 10-30%*.



Bifacial Power

In contrast to conventional modules, PANDA BIFACIAL modules generate energy from both sides. As the backside makes use of the reflected and scattered light from the surroundings, the modules can yield up to 30% power more, depending on the albedo.



High Yield

Once used, PANDA BIFACIAL modules generate more energy, because of low LID, good low-light performance and temperature coefficient of N-type monocrystalline silicon solar cells.



High Power Output

5 Bus-bar half cells and series & parallel electrical structure can reduce CTM loss and increase module output power.



Durability

Durable PANDA BIFACIAL modules work well in muggy conditions, and independently tested for harsh environmental conditions beyond IEC standards such as exposure to salt mist, ammonia or known PID risk factors.



Optimal Self-cleaning

Optimal self-cleaning due to frameless module design.

Yingli Green Energy

Yingli Green Energy Holding Company Limited, known as "Yingli Solar", is one of the world's leading solar panel manufacturers with the mission to provide affordable green energy for all. Deploying more than 17 GW solar panels worldwide, Yingli Solar makes solar power possible for communities everywhere by using our global manufacturing and logistics expertise to address unique local challenges.

*Depending on the environmental condition of installation.

PANDA BIFACIAL 144HCL

ELECTRICAL PERFORMANCE

Electrical parameters at Standard Test Conditions (STC)

Module type	YLxxxCG2536L-2 1/2 (xxx=P _{max})						
Power output	P _{max}	W	360	355	350	345	340
Power output tolerance	ΔP _{max}	W	0 / + 5				
Module efficiency	η _m	%	17.8	17.5	17.3	17.0	16.8
Voltage at P _{max}	V _{mpp}	V	39.8	39.5	39.2	38.7	38.5
Current at P _{max}	I _{mp}	A	9.05	8.99	8.94	8.92	8.85
Open-circuit voltage	V _{oc}	V	47.2	47.1	46.6	46.3	46.0
Short-circuit current	I _{sc}	A	9.47	9.43	9.39	9.37	9.35

STC: 1000W/m² irradiance, 25°C cell temperature, AM1.5 spectrum according to EN 60904-3.
Average relative efficiency reduction of 1.9% at 200W/m² according to EN 60904-1.

Electrical parameters at Nominal Module Operating Temperature (NMOT)

Power output	P _{max}	W	272.7	268.9	265.1	261.3	257.5
Voltage at P _{max}	V _{mpp}	V	37.8	37.5	37.2	36.8	36.5
Current at P _{max}	I _{mp}	A	7.21	7.16	7.12	7.11	7.05
Open-circuit voltage	V _{oc}	V	44.8	44.7	44.2	43.9	43.6
Short-circuit current	I _{sc}	A	7.62	7.59	7.55	7.54	7.52

NMOT: temperature near maximum power point at 800W/m² irradiance, 20°C ambient temperature, 1m/s wind speed.

THERMAL CHARACTERISTICS

Nominal module operating temperature	NMOT	°C	39±2
Temperature coefficient (P _{max})	γ _{Pmax}	%/°C	-0.38
Bifaciality (P _{max})	φ _{Pmax}	%	82.0
Temperature coefficient (V _{oc})	β _{Voc}	%/°C	-0.30
Bifaciality (V _{oc})	φ _{Voc}	%	99.3
Temperature coefficient (I _{sc})	α _{Isc}	%/°C	0.04
Bifaciality (I _{sc})	φ _{Isc}	%	81.5

OPERATING CONDITIONS

Max. system voltage	1500V _{DC}
Max. series fuse rating	20A
Limiting reverse current	20A
Operating temperature range	-40°C to 85°C
Max. snow load, front*	5400Pa
Max. wind load, back	2400Pa
Max. hailstone impact (diameter / velocity)	25mm / 23m/s
Fire class	A

*Load bearing capacity depends on installation.

CONSTRUCTION MATERIALS

Front and back cover (material / thickness)	low-iron semi-tempered glass / 2.5mm x 2
Cell (quantity / material / dimensions / number of busbar)	144 / monocrystalline silicon / 156.75mm x 78.38mm / 5
Frame	N / A
Junction box (protection degree)	≥ IP67
Cable (length / cross-sectional area)	350mm / 4mm ²
Plug connector (type / protection degree)	RH05-8 / IP67

* Due to continuous innovation, research and product improvement, the specifications in this product information sheet are subject to change without prior notice. The specifications may deviate slightly and are not guaranteed.

* The data do not refer to a single module and they are not part of the offer, they only serve for comparison to different module types.

QUALIFICATIONS & CERTIFICATES

IEC 61215, IEC 61730, CE, ISO 9001:2008, ISO 14001:2004, BS OHSAS 18001:2007, SA 8000




GENERAL CHARACTERISTICS

Dimensions (L / W / H)	1950mm / 1040mm / 6mm
Weight	27.9kg

PACKAGING SPECIFICATIONS

Number of modules per pallet	33
Number of pallets per 40' container	24
Packaging pallets dimensions (L / W / H)	2070mm / 1140mm / 1230mm
Pallet weight	980kg

Unit: mm



Warning: Read the Installation and User Manual in its entirety before handling, installing and operating Yingli Solar modules.

Yingli Partners:

Yingli Green Energy Holding Co., Ltd.

service@yingli.com

Tel: +86-312-2188055

YINGLISOLAR.COM

