

MonoPower Micro

ASP M5-72 Series 190W-215W

Monocrystalline PV-module



QUALITY & RELIABILITY

Best raw materials, optimized production process and accurate testing makes the quality difference



GERMAN ENGINEERING

Best design by the art of German engineering



SAVE INVESTMENT

Product warranty of 12 years
and performance warranty of 25 years



POSITIVE PERFORMANCE TOLERANCE

Up to +5 W plus-tolerance on output




FOR ALL ENVIRONMENTAL CONDITIONS

Resistant against PID, sand, salt and ammonia



STABLE AND STRONG

Capable to bear heavy snow loads up to 5400 Pa
and wind loads up to 2400 Pa




12 YEARS
PRODUCT WARRANTY

OUR PERFORMANCE GUARANTEE



25 YEARS
PERFORMANCE GUARANTEE




CERTIFICATES



IEC 61215
IEC 61730
PERIODICAL
INCEPTION



PID RESISTANT
SALT MIST RESISTANT
SAND RESISTANT
CORROSIVE GAS (NH₃)



SOLAR PLANET
Enjoy the quality difference

MonoPower Micro Module

ASP M5-72 Series 190W-215W

TECHNICAL DATA

ASP190M5-72 ASP195M5-72 ASP200M5-72 ASP205M5-72 ASP210M5-72 ASP215M5-72

Maximum power	P _{max} (Wp)	190	195	200	205	210	215
Maximum power voltage	V _{mp} (V)	38.08	38.19	38.30	38.40	38.51	38.62
Maximum power current	I _{mp} (A)	4.99	5.11	5.22	5.34	5.45	5.57
Open-circuit voltage	V _{oc} (V)	45.88	45.98	46.10	46.20	46.31	46.42
Short-circuit current	I _{sc} (A)	5.61	5.66	5.70	5.75	5.79	5.84
Module efficiency	%	14.88	15.27	15.67	16.06	16.45	16.84
Power tolerance	P _{max} (W)	0 / +5					
Maximum system voltage DC	V	1000					
Operating temperature	°C	40 to +85					
Temperature coefficients of P _{max}	%/°C	-0.36					
Temperature coefficients of V _{oc}	%/°C	-0.36					
Temperature coefficients of I _{sc}	%/°C	0.06					
Nominal operating cell temp. (NOCT)	°C	45 ± 2					

The electrical data apply to standard test conditions (STC): Irradiance of 1000 W/m² with spectrum AM 1.5 and a cell temperature of 25°C.


MATERIAL CHARACTERISTICS

Cell type	Monocrystalline 125 x 125 mm
No. of cells	72 (6 x 12)
Dimensions	1580 x 808 x 35 mm
Weight	14 kg
Junction box	IP 67 rated
Output cable	4.0 mm ² , 900 mm
Connector type	MC 4 / MC 4 compatible
Hail resistance	Max. Ø 25 mm, at 23 m/s
Wind load	2400 Pa / 244 kg / m ²
Mechanical load	5400 Pa / 550 kg / m ²

PACKING INFORMATION

Packing configuration	70 pcs / double pallet
Loading capacity	980 pcs / 40 HQ
Size / pallet	1630 x 1135 x 2325 mm
Weight	1080 kg / pallet

DRAWINGS



Alpha Solar Planet GmbH
Schwalbenweg 1 g, 86343 Königsbrunn

Tel.: +49 8231 99190 70
Fax: +49 8231 99190 89

E-mail: info@a-s-p.solar
Web: www.a-s-p.solar

