



#### 电性能参数 Electrical Characteristics

最大功率 (Pmax)	195W
最佳工作电压 (Vmp)	19.9V
最佳工作电流 (Imp)	9.8A
开路电压 (Voc)	22.63V
短路电流 (Isc)	10.9A
开路电压温度系数	- (80±10) mV/°C
短路电流温度系数	(0.065±0.015) %/°C
峰值功率温度系数	- (0.5±0.05) %/°C
NOTC	47±2°C
工作温度	-40°C 85°C
最大系统电压	1000V DC
输出功率公差	±5

Maximum power at STC (Pmax)	195W
Optimum operating voltage (Vmp)	19.9V
Optimum operating current (Imp)	9.8A
Open-circuit voltage (Voc)	22.63V
Short-circuit current (Isc)	10.9A
Temperature coefficient of Voc	- (80±10) mV/°C
Temperature coefficient of Isc	(0.065±0.015) %/°C
Temperature coefficient of Pmax	- (0.5±0.05) %/°C
NOTC (Air20°C,Sun0.8km/m <sup>2</sup> ,Wind1m/s)	47±2°C
Operating temperature	-40°C 85°C
Max. system voltage	1000V DC
Power tolerance	±5

高转换率、高效率输出  
卓越的弱光效应  
采用高透光率优质钢化玻璃  
持久耐用阳极氧化铝合金边框  
特有的技术避免框架内积水冻结和变形  
独特工艺使组件美观坚固抗风雪，安装方便

High efficiency.  
Outstanding low-light performance.  
High transmission tempered glass.  
Durable anodized aluminum frame.  
Efficient protection from frame deformation and water accumulation.  
Rugged design to withstand high wind pressure and snow load, easy installation.

#### 电池板 (单晶)

SOLAR PANEL  
MONO-CRYSTALLINE

12V/195W

