## Intelligent anti-polar sine wave inverter(SQA-1000W)



		ort School Co.	100 F 100
特性:			
*	Use it conveninet and quickly , easy for installation , connect storage battery can be used , daily maintence free		
*	Magnesium alloy aluminum shell , brand new imported componets, reliable quality assured		
*	SMT process , make the inverter smaller , lighter weight , high reliability , solder joint defect rate is low, excellent high frequency characteristics, reducing the eletromagnetic and radio frequency interference		
*	overtemperature protection , AC low-voltage protection , AC high-voltage protection, over load protection, short-circuit protection, ensure inverter in the process of using comprehensive protection, it can extend of the life of the power inverter.		
*	screw terminal, connection firmer, input is more stable, high-performance intelligent temperature control cooling fan ,more save electricity, save the loss, independent power switch, it also using the software testing the soft boot, to protect your unit and applicances, double indicator lights, multi-purpose socket, reasonable layout is compatibale with the most of the plug on market.		
*	Using computer programming technology ,it also has program control circuit, to make the outlet current more stable		
*	High-precision double-sided circuit board , the plug-in welding separate with the SMT components , so it can mutual interference, reasonable design, exquisite workmanship, provides high quality electric current , the coversion rate of 88% or more		
Pı	roduct Model	SQA-1000A	SQA-1000B
Input	Input voltage	12VDC	24VDC
	Input voltage	10.5~15.0 VDC	21.0~30.0 VDC
	Alarm protection	10.5VDC	21.0VDC
	Low-voltagve protection	10. OVDC	20.0VDC
	over-voltage protection	15. 5VDC	31.0VDC
Output	Rate power	1000 Watt	
	Peak power	2000 Watt	
	Output frequency	50Hz ± 0.1% or 60Hz ± 0.1% (optional)	
	Output voltage	100~120VAC / 200~240VAC (optional)	
Conversion efficiency		88% (full load)	
No load current		< 0.3A	
Operating temperature range		−10°C to +55°C	
Operationg humidity range		20%~70%	
Storage temperature range		-30℃ to +70℃	
Type of coling		Intelliget temperature air cooling straight rotary air cooling(optional)	
Packing information	Product size	273*121*68MM	273*121*68MM
	Product net weight	1.41KG	1.43KG
	Manner of packing	color box 285*170*80MM	color box 285*170*80MM
	single packing weight	1.69KG	1.71KG
	Carton size	35.5*29.5*43CM	35.5*29.5*43CM
	Kg/size	17.51KG	17.68KG
	Number of carton packing	10PCS/carton	10PCS/carton
Protection function		battery anti-polar protection short circuit protection over load protection over temperature protection high/low voltage	
Range of applicantion		·digital camera ·TV ·cell phone ·DVD · electric detection field equipment	