

Pure Sine Wave Inverter

OP-SP-4000S OP-SP-5000S OP-SP-6000S



OP-SP-4000S



OP-SP-5000S



OP-SP-6000S

技术参数 Technical parameter

型号 Model	OP-SP-4000S	OP-SP-5000S	OP-SP-6000S	
输入 Input	直流电压 DC voltage			
	12V or 24V or 48V or 110V			
	直流电压范围 Voltage range			
	10-15VDC or 21-30VDC or 42-60VDC or 100-120VDC			
	空载电流 No load current draw	<1.86	<1.9	<1.86
	效率 Efficiency	> 85%		
	直流连接 DC connection	电线 Cables With Clips		
输出 Output	输出电压 AC voltage			
	100/110/120VAC or 220/230/240VAC			
	额定功率 Continuous power	4000W	5000W	6000W
	瞬间功率 Surge power	8000W	10000W	12000W
	输出波形 Wave form	纯正弦波 Pure sine wave		
	输出频率 Frequency	50Hz/60Hz		
	波形失真 Wave distortion	3%		
保护 Protection	低压报警 Low voltage alarm	10VDC ± 0.5V or 20.5VDC ± 1V or 44VDC ± 1V or 100VDC ± 1V		
	低压关断 Low voltage shut down	9.5VDC ± 0.5V or 19.5VDC ± 1V or 42VDC ± 1V or 96VDC ± 5V		
	过载 Overload	输出关闭 Shut off output		
	过压 Over voltage shut down	15.5V or 30.5V or 61.2V or 120V		
	过热 Over thermal	自动输出关闭 Shut off output automatically		
	工作温度 Working temperature	-10°C 到 +50°C之间 -10°C to +50°C		
	湿度 Working humidity	20% ~ 90% 无冷凝 No condensation RH		
	储存温度 Storage temperature	-30°C 到 +70°C之间 -30°C to +70°C		
包装 Package	产品尺寸 Machine size (mm)	435 × 199 × 146	544 × 199 × 146	544 × 199 × 146
	包装尺寸 Packing size (mm)	565 × 285 × 235	665 × 285 × 235	865 × 285 × 235
	净重 Net weight (kg)	9.7	11.9	12.1
	毛重 Gross weight (kg)	11.65	13.7	15
	包装方式 Packing mode	纸箱包装 Carton packaging		
其他 Other	启动 Start	软启动 Soft start		
	冷却方式 Cooling ways	智能冷却风扇 Intelligent cooling fan		

备注：以上数据仅供参考。如有变动，请参阅最新产品使用说明书。

Note: The above parameters are for reference only. If have any changes, subject to the manufacturers of the latest data prevail.