

HYECO

INVERTER GENERATOR

- ▶ **Light weight, small size**
- ▶ **More quietness**
- ▶ **Pure sine wave output**
- ▶ **Low fuel consumption**



Pure sine wave output

HyECO Power Tech Co., Ltd.

Power System Division: 12 Beiqian Lane, Industrial Park, Suzhou, Jiangsu 215000, China.

Tel: (86-512) 6761 2708 Fax: (86-512) 6281 8406 E-mail: henrykoo@hypetek.com

Engine & Garden Tools Division: 7558 Mudong Rd., Hengjing, Wuzhong, Suzhou, Jiangsu 215103, China.

Tel: (86-512) 6620 9305 Fax: (86-512) 6620 2718 E-mail: global@hypetek.com www.hypetek.com

Inverter Generator

Specifications

Generator	Generator Type	Multipole field rotation type
	Rated Voltage(V)	230/120
	AC Voltage Frequency (Hz)	50/60
	Rated power(kW)	3.0
	Max power(kW)	3.3
	Rated speed(r/min)	3600
	Waveform distortion(THD) (%)	≤ 3
	Power factor	1.0
	DC Voltage(V)	12
	DC Current(A)	8.0
	Overload Capacity	Yes
	Oil Alert	Yes
Fuel Capacity(L)	10	
Engine	Engine type	Air - cooled 4 - stroke OHV
	Engine model	HK210
	Displacement(cc)	210
	Bore x Stroke(mm)	70 X 54
	Compression Ratio	8.5 : 1
	Oil Capacity(L)	0.5
	Spark plug	LD:F7RTC
	Governor	Electric control type
	Starting System	Recoil/Electric
	Oil used	SAE15W- 40
	Fuel used	Automotive unleaded gasoline with a pump octane rating of 86 or higher



INVERTER GENERATOR