

USP 300W/400W/500W/600W/700W/1000W/1500W/2000W

Model		300W	400W	500W	600W	700W	1000W	1500W	2000W	
Input	Rated capacity	300W	400W	500W	600W	700W	1000W	1500W	2000W	
Input	peak power	600W	800W	1000W	1200W	1500W	2000W	3000W	4000W	
Input	Commercial Power range (VAC)	100/110/120/127/220/230 (+25%, -35%)								
Battery	DC Voltage	12/24VDC						24/48VDC		
Output	AVR voltage range (VAC)	110/120/127/220/230/240±10% (Auto-sensing)								
	over voltage protection	15V/30V						30V /60V		
	under voltage protection	10.5V/21V ±1V						21V/42V ±1V		
	Transfer time	Typical:5ms (Including detection time)								
Output	waveform	Pure sine wave								
	Frequency	Commercial power supply:shared frequency with the commercial inversion state:60/50±0.5								
Temperature	Operating Temperature	0°C~70°C								
Appearance	External Size (mm) (L*W*H)	320*150*210						380*195*310		
	Gross Size (mm) (L*W*H)	494*420*345 (2PCS)						532*468*335 (1PCS)		
	Net weight(kg)	7	8	9	10	11.5	15	23	26	
	Gross weight(kg)	16	18	20	22	23	30	25	28	
protection	overload	IPS automatically shut down if overload exceeds 120% of normal value for 10 seconds, IPS automatically resume work if overload comes to rated load.								
Battery	Type	Sealed, maintenance-free lead acid								
	Recharge current	15A (Maximum)								
	Battery protection	Automatic self-test, discharge protection, over-charge protection, smart management system.								