

TECHNICAL CHARACTERISTICS

HEC-US V1500 - 690V

NORTH AMERICA

	FRAME 1	FRAME 2	FRAME 3	FRAME 4	FRAME 5	
NUMBER OF MODULES	3	4	5	6	7	
REFERENCE	FS1275CU15	FS1700CU15	FS2125CU15	FS2550CU15	FS3000CU15	
OUTPUT	AC Output Power (kVA/kW) @50°C ^[1]	1275	1700	2125	2550	3000
	AC Output Power (kVA/kW) @25°C ^[1]	1530	2040	2550	3060	3500
	AC Output Power (kW) @50°C; PF=0.9	1150	1530	1910	2250	2700
	Max. AC Output Current (A) @25°C	1285	1710	2140	2570	3000
	Operating Grid Voltage (VAC)	690V ±10%				
	Operating Grid Frequency (Hz)	60Hz				
	Current Harmonic Distortion (THDi)	< 3% per IEEE519				
	Power Factor (cosine phi) ^[2]	0.0 leading ... 0.0 lagging / Reactive Power injection at night				
	Power Curtailment	0...100% / 0.1% Steps				
INPUT	MPPT @full power (VDC) ^[1]	976V - 1310V				
	Maximum DC voltage	1500V				
	Minimum Start Voltage	1100V - User configurable				
	Max. DC continuous current (A)	1600	2140	2675	3210	3745
	Max. DC short circuit current (A)	2320	3100	3880	4650	5450
EFFICIENCY & AUXILIARY SUPPLY	Efficiency (Max) (η)	98.5%	98.7%	98.7%	98.7%	98.7%
	CEC (η)	98.0%	98.5%	98.5%	98.5%	98.5%
	Max. Standby Consumption (Pnight)	< approx. 50W/per module				
	Control Power Supply	120V / 208VAC-6kVA power supply available for external equipment (optional)				
CABINET	Dimensions [WxDxH] [inches]	119.6"x37.2"x86.5"	147.6"x37.2"x86.5"	175.7"x37.2"x86.5"	203.8"x37.2"x86.5"	231.9"x37.2"x86.5"
	Dimensions [WxDxH] [mm]	3038x945x2198	3751x945x2198	4464x945x2198	5177x945x2198	5890x945x2198
	Weight (kg)	2635	3290	3945	4600	5255
	Weight (lbs)	5809	7253	8697	10141	11585
	Air Flow	Bottom intake. Exhaust top rear vent.				
	Type of ventilation	Forced air cooling				
ENVIRONMENT	Degree of protection	NEMA 3R				
	Permissible Ambient Temperature	-31°F to +140°F, -35°C ^[3] to +60°C / Active Power derating >50°C/122°F				
	Relative Humidity	0% to 100% non condensing				
	Max. Altitude (above sea level)	2000m / >2000m power derating (Max. 4000m)				
	Noise level ^[4]	< 79 dBA				
CONTROL INTERFACE	Interface	Graphic Display (inside cabinet) / Optional Freesun App				
	Communication protocol	Modbus TCP				
	Power Plant Controller	Optional				
	Keyed ON/OFF switch	Standard				
	Digital I/O	User configurable				
	Analog I/O	User configurable				
PROTECTIONS	Ground Fault Protection	Floating PV array: Isolation Monitoring per MPP NEC2014 Grounded PV Array: GFDI protection Optional PV Array transfer kit: GFDI and Isolation monitoring device				
	Humidity control	Active Heating				
	General AC Protection & Disconn.	Circuit Breaker				
	General DC Protection & Disconn.	External Disconnecting Unit Cabinet				
	Module AC Protection & Disconn.	AC contactor & fuses				
	Module DC Protection	DC fuses				
	Overvoltage Protection	AC and DC protection (type 2)				
CERTIFICATIONS	Safety	UL 1741, CSA 22.2 No.107.1-01, UL62109-1				
	Utility interconnect	UL 1741SA-Sept. 2016 / IEEE 1547.1-2005				

[1] Values at 1.00·Vac nom and cos Φ= 1.

Consult Power Electronics for derating curves.

[2] Consult P-Q charts available: $Q(kVar)=\sqrt{(S(kVA))^2-P(kW)^2}$.

[3] Heating resistors kit option below -20°C.

[4] Readings taken 1 meter from the back of the unit.