

Solis-1P(2.5-6)K-4G

Solis 4G Single Phase Inverters



Features:

- ▶ Over 98.1% Max. efficiency
- ▶ Super high frequency switching technology
- ▶ Wide voltage range and low startup voltage
- ▶ Dual MPPT design with precise MPPT algorithm
- ▶ Intergrated Export Power Manager(EPM)
- ▶ Compact and lightweight
- ▶ Friendly and adaptable connection to the grid



Model:

Solis-1P2.5K-4G
Solis-1P3.6K-4G
Solis-1P4.6K-4G
Solis-1P6K-4G

Solis-1P3K-4G
Solis-1P4K-4G
Solis-1P5K-4G

Datasheet

Model Name	Solis-1P2.5K-4G	Solis-1P3K-4G	Solis-1P3.6K-4G	Solis-1P4K-4G	Solis-1P4.6K-4G	Solis-1P5K-4G	Solis-1P6K-4G
------------	-----------------	---------------	-----------------	---------------	-----------------	---------------	---------------

Input DC

Max. input power	3kW	3.5kW	4.2kW	4.6kW	5.3kW	5.8kW	6.6kW
Max. input voltage	550V	600V					
Rated voltage	250V	330V					
Start-up voltage	60V	120V					
MPPT voltage range	50-450V	90-520V					
Max. input current	11A/11A						
Max. Short Circuit current	17.2A/17.2A						
MPPT number/Max. input strings number	2/2						

Output AC

Rated output power	2.5kW	3kW	3.6kW	4kW	4.6kW	5kW	6kW
Max. apparent output power	2.8kVA	3.3kVA	4kVA	4.4kVA	5kVA	5kVA	6kVA
Max. output power	2.8kVA	3.3kW	4kW	4.4kW	5kW	5kW	6kW
Rated grid voltage	1/N/PE, 220V/230V						
Rated grid frequency	50Hz/60Hz						
Rated grid output current	11.4A/10.9A	13.6A/13.0A	16.0A/15.7A	18.2A/17.4A	20.9A/20.0A	22.7A/21.7A	27.3A
Max. output current	13.3A	15.7A	16.0A	21.0A	23.8A	25.0A	27.3A
Power Factor	>0.99 (Adjustable from 0.8 leading to 0.8 lagging)						
THDi	<3%						

Efficiency

Max. efficiency	97.8%			98.1%			
EU efficiency	97.1%			97.3%			

Protection

DC reverse-polarity protection	Yes
Short circuit protection	Yes
Output over current protection	Yes
Surge protection (DC/AC)	Yes
Grid monitoring	Yes
Islanding protection	Yes
Temperature protection	Yes
Integrated DC switch	Optional

General Data

Dimensions (W*H*D)	310mm*543mm*160mm
Weight	11.5kg
Topology	Transformerless
Self consumption	<1W (Night)
Operating ambient temperature range	-25~60°C
Relative humidity	0~100%
Ingress protection	IP65
Cooling concept	Natural convection
Max. operation altitude	4000m
Grid connection standard	VDE-AR-N 4105, VDE V 0124, VDE V 0126-1-1, UTE C15-712-1, NRS 097-1-2, G98, G99, EN 50549-1/-2, RD 1699, UNE 206006, UNE 206007-1, IEC61727
Safety/EMC standard	IEC 62109-1/-2, IEC62116, EN 61000-6-2/-3

Features

DC connection	MC4
AC connection	IP67 Rated plug
Display	LCD, 2×20 Z.
Communication	RS485; WiFi/GPRS (optional)