

# Solis-(40-60)K, Solis-(50-70)K-HV

Solis Three Phase Inverters



## Features:

- ▶ Over 99% Max. efficiency
- ▶ Wide voltage range and low startup voltage
- ▶ Four MPPT input, each rated current is 28.5A, compatible with high power module
- ▶ THDi<3%, low harmonic distortion against grid
- ▶ Anti-resonance, single transformer can connect 6M+ in parallel
- ▶ Perfect commercial site monitoring solution
- ▶ Intelligent redundancy fan



## Model:

- 400V: Solis-40K      Solis-50K      Solis-60K-4G  
480V: Solis-50K-HV   Solis-60K-HV   Solis-70K-HV-4G

## Datasheet

Model Name	Solis-40K	Solis-50K	Solis-50K-HV	Solis-60K-HV	Solis-60K-4G	Solis-70K-HV-4G
<b>Input DC</b>						
Max. input power	48kW	60kW	60kW	72kW	72kW	84kW
Max. input voltage			1100V			
Rated voltage	600V	600V	720V	720V	600V	720V
Start-up voltage			200V			
MPPT voltage range			200-1000V			
Max. input current	4*22A	4*28.5A	4*22A		4*28.5A	
Max. Short Circuit current	4*34.3A	4*44.5A	4*34.3A		4*44.5A	
MPPT number/Max. input strings number	4/8	4/12	4/8		4/12	
<b>Output AC</b>						
Rated output power	40kW	50kW	50kW	60kW	60kW	70kW
Max. apparent output power	44kVA	55kVA	55kVA	66kVA	66kVA	77kVA
Max. output power	44kW	55kW	55kW	66kW	66kW	77kW
Rated grid voltage	3/N/PE, 220/380V, 230/400V		3/PE, 480V		3/N/PE, 220/380V, 230/400V	3/PE, 480V
Rated grid frequency			50Hz/60Hz			
Rated grid output current	60.8A/58A	76.0A/72.2A	60.2A	72.2A	91.2A/86.6A	84.2A
Max. output current	66.9A	83.3A	66.2A	80A	100A	92.6A
Power Factor	>0.99 (Adjustable from 0.8 leading to 0.8 lagging)					
THDi	<3%					
<b>Efficiency</b>						
Max. efficiency	98.8%		99.0%		99.0%	
EU efficiency	98.4%		98.7%		98.5%	
<b>Protection</b>						
DC reverse-polarity protection	Yes					
Short circuit protection	Yes					
Output over current protection	Yes					
Surge protection (DC/AC)	Yes					
Grid monitoring	Yes					
Islanding protection	Yes					
Temperature protection	Yes					
Integrated DC switch	Optional					
<b>General Data</b>						
Dimensions (W*H*D)	630mm*700mm*357mm					
Weight	61kg	63kg	61kg		63kg	
Topology	Transformerless					
Self consumption	<1W (Night)					
Operating ambient temperature range	-25~60°C					
Relative humidity	0~100%					
Ingress protection	IP65					
Cooling concept	Natural convection	Intelligent redundant fan-cooling	Natural convection		Intelligent redundant fan-cooling	
Max. operation altitude	4000m					
Grid connection standard	VDE-AR-N 4105, VDE V 0124, VDE V 0126-1-1, UTE C15-712-1, NRS 097-1-2, G98, G99, EN 50549-1/-2, RD 1699, UNE 206006, UNE 206007-1, IEC61727, DEWA					
Safety/EMC standard	IEC 62109-1/-2, IEC62116, EN 61000-6-2/-4					
<b>Features</b>						
DC connection	MC4					
AC connection	OT Terminal connectors					
Display	LCD, 2x20 Z.					
Communication	RS485; WiFi/GPRS (optional)					