

800W Pure sine wave inverter

Product Features:

- Pure sine wave output waveform
- Soft start: smooth start-up of appliances
- DC/AC isolated
- Input protection: Reverse polarity(Fuse), low voltage, over voltage
- Output protection: short circuit, overload, over temperature
- Low interference technology
- two color(green and red) indicators show normal and fault status
- The surge power twice as rated power
- remote control and monitor with cable(3M) or without cable(blue tooth, 10m)
- Thermal methods: cooling fans, automatic on when inner temperature $\geq 45^{\circ}$
- CE-EMC/LVD, RoHS , FCC approved



Model	PUS800-12-110	PUS800-12-220	PUS800-24-110	PUS800-24-220	PUS800-48-110	PUS800-48-220		
Continuous Output Power	800W							
Peak Power	1600W (<5ms)							
DC Input Voltage	12V		24V		48V			
AC Output Voltage	110AC \pm 10%	220VAC \pm 5%	110AC \pm 10%	220VAC \pm 5%	110AC \pm 10%	220VAC \pm 5%		
No-load Current	$\leq 0.8A$							
AC Output Frequency	50HZ \pm 1%/60HZ \pm 1%							
AC Output Waveform	Pure Sine Wave							
Waveform Distortion	THD<3%(Linear load)							
Efficiency	$\geq 88\%$							
Low Voltage Alarm	10.5 \pm 0.3V		21 \pm 0.6V		41.8 \pm 1.2V			
Low Voltage Shutdown	9.5 \pm 0.2V		19 \pm 0.3V		38 \pm 0.4V			
Over Voltage Protection	15.5 \pm 0.5V		31 \pm 1V		62 \pm 2V			
Low Voltage Recovery	11.8 \pm 0.3V		23.6 \pm 0.4V		47.2 \pm 0.8V			
Over Voltage Recovery	15.7 \pm 0.3V		31.8 \pm 0.4V		63 \pm 1V			
Over Load Protection	120%~125%							
Protective Function	Low voltage: LED red light, Buzzer alarm, automatic recovery							
	Over voltage: LED red light, automatic recovery, Buzzer alarm							
	Over load: LED red light, automatic shut down, need restart, Buzzer alarm							
	Over temperature: LED red light, Buzzer alarm, automatic recovery							
	Short circuit (within 2s): automatic recovery							
	Input reverse connection: fuse burn-out							
Working Temp.	-25 $^{\circ}$ C-50 $^{\circ}$ C							
Storage Temp.	-20 $^{\circ}$ C-85 $^{\circ}$ C							
Working Altitude	$\leq 3000m$							
Machine Size	240*145*70mm							
Net Weight	1.8 \pm 0.2kg							
Packing Size	420*355*420mm							
Gross Weight	2.1 \pm 0.2kg							
QTY	6pcs/box							
Accessories	1 x inverter, 1 x fuse, 1 x instruction book, 1 x connection wire,(optional external LCD screen with wire connection or wireless external LCD screen)							
Packing	Poly bag+inner box+carton							
Socket types								
	A	B	C	D	E	F	G	H
	USA	AUSTRALIA	UNIVERSAL	U.K	FRANCE	GERMANY	Japan	Brazil