

# Equinox 250kW UL

Model Number : EQX0250UV480T

PV Inverters

**Peak Efficiency of 97.2%**  
**Next Generation Modular Design**  
**Wide Thermal Operating Range**

## Streamline Design

With all components encased in a single enclosure. Equinox PV inverters are easy to install, operate and maintain.

## Advanced Utility-Ready Features

- Remote control of real and reactive power
- Low-voltage ride through
- Power factor control
- Simplified grid interconnection
- Fast communication
- Easily integrated into SCADA systems through standardized communication interfaces

## Rugged Design

- Wide thermal operating range:  
-22°F to +140°F (-30°C to +60°C)
- Support for external temperatures as low as -40°F with optional Winter climate package
- Designed for optimal performance in Desert, Topical and Winter climates

## Industrial-Grade Engineering

- Fully outdoor rated solution (no concrete station required)
- NEMA 3R enclosure for maximum protection and longevity
- Double wall enclosure eliminates external air circulation from inside inverter
- Solar shields attached to exterior of enclosure dissipate solar radiation, reduce heat buildup



## Profitable PV Power

The Satcon® Equinox™ inverter has a significant impact on the profitability dynamic of large-scale solar power systems. With its system intelligence, next-generation MPPT technology, and industrial-grade engineering, the Equinox inverter maximizes system uptime and power production, even in the harshest environments.

## Rugged Design

Equinox features a NEMA 3R enclosure, ensuring protection and longevity. It features a wide thermal operating range from -22° F to +140° F. With the optional Winter climate package, it supports temperatures as low as -40° F with an optional heater.

## Industrial-Grade Engineering

As a fully outdoor rated solution, Equinox does not require an external climate controlled enclosure or concrete station, reducing both cost and space requirements. Equinox's double wall enclosure cooling system eliminates the need for external air circulation inside the inverter, reducing contaminants and improving cooling performance.

## Increased PV Plant Yield

Equinox, Satcon's next-generation inverter design, features best-in-class peak efficiency of 97.2% to provide you with the highest levels of system performance and uptime.

## Advanced Utility-Ready Features


Equinox's advanced utility-ready features enable remote control of real and reactive power, low-voltage ride through and power factor control. Equinox provides for simplified grid interconnection and supports fast communications, allowing it to be easily integrated into SCADA systems through standardized communication interfaces.

## Commercial and Utility-Scale

Many of the world's largest solar power installations depend on Satcon Equinox PV inverters to provide efficient and stable power—even in the harshest climates.

## Proven Performance

The proven leader in solar inverter solutions for commercial installations, Satcon sets the standards for efficient large-scale power conversion



**Satcon**  
Utility-Ready Solar Inverters

# Equinox 250kW UL

## Streamlined Design

With all components encased in a single enclosure, Equinox is easy to install, operate and maintain.

## Outdoor Construction

- Rugged cabinet for all environments
- Dual cooling fans


## Easy Maintenance

- Modular components make service efficient
- Convenient access to all components
- Customizable large in-floor cable gland plates make installation of DC and AC cables easy
- Integrated DC two-pole disconnect switch isolates the inverter, with the exception of the GFDI (Ground Fault Detection and Interruption) circuit, from the photovoltaic power system to allow inspection and maintenance

## Proven Reliability

Rugged and reliable, Equinox PV inverters are engineered from the ground up to meet the demands of large-scale installations.

Specifications	250 kW
<b>Input Parameters</b>	
Input Voltage Range	500 – 850 VDC
Maximum Array Input Voltage	1000 VDC
Maximum Operating Input Current <sup>1</sup>	567ADC
PV Array Configuration	Negative/ Positive
<b>DC Input Combiner Options</b>	
Combiner Bus Bar Input	5
Fuse	200A
<b>Transformer</b>	
Integrated Transformer	Yes
<b>Efficiency</b>	
Maximum <sup>2</sup>	97.0%
CEC Efficiency <sup>3</sup>	96.5%
<b>Output Parameters</b>	
Nominal Power	250 kW
Nominal Output Voltage	480 VAC
Output Voltage Range, [-12%/10%]	422-528 VAC
Nominal Output Current / Phase	301 A
Standby Consumption (tare losses including control power and aux. )	100 W
Nominal Output Frequency, 3-Phase	60 Hz
Maximum Harmonic Distortion	< 3% THD
Power Factor, Full Load	> 99%
Dynamic Power Factor Control	+/- 0.8
Power Curtailment	0-100%, 1% step
<b>Environment</b>	
Operating Temp Range	-30 °C ~ +60 °C
Storage Temperature Range	-30 °C ~ +70 °C
Cooling	Forced Air
Noise Level (Distance of 3m)	< 65 dB(A)
Relative Humidity (Non-Condensing)	0 ~ 95%
Elevation (Maximum) <sup>4</sup>	4,000 m



**Satcon**<sup>®</sup>

Utility-Ready Solar Inverters

# Equinox 250kW UL

Specifications	250 kW
<b>Enclosure</b>	
Dimensions (H x W x D) <sup>3</sup>	2103mm x 2970mm x 945mm
Weight <sup>3</sup>	2400kg
Finish	RAL 7035
Hood and Base Trim Finish	RAL 5001
Protection Rating	NEMA 3R
<b>Warranty and Services</b>	
Five Year Warranty	Standard
Extended Warranty (1 and 5 year warranty)	Optional
Preventive Maintenance Agreement	Optional
<b>Communication Interface</b>	
Modbus RS485	Standard
Modbus TCP/IP	Optional
<b>Monitoring</b>	
PV Zone	Optional
Third Party Compatibility	Standard
<b>Regulations and Standards Conformity</b>	
UL1741, CSA 107.1, IEEE1547, IEEE1547.1	Standard
IEEE C62.41.2, IEEE C62.45	Standard
IEEE C37.90.1, IEEE C37.90.2	Standard

## Global Headquarters

5<sup>th</sup> Floor, No. 10 Factory Building ,  
and No. 2 Plant, Greatwall  
Industrial Complex, Shuitian  
Community, Shiyan Town, Bao'an  
District, Shenzhen 518108, China  
P: +86 755 3338 8008  
F: +86 755 8959 5683  
E: [sales@satcon.com](mailto:sales@satcon.com)

[www.Satcon.com](http://www.Satcon.com)  
[www.cecgwenergy.com](http://www.cecgwenergy.com)

1. Calculated at nominal power and minimum DC voltage
2. Calculated without auxiliary power
3. Preliminary value
4. Operation above 3,281ft.(1,000m) results in a decrease in the maximum ambient temperature for full power operation. For each additional 3,281ft (1,000m) in elevation, there is approximately a +4.5°F (+2.5°C) decrease in the maximum ambient temperature for full power operation.

Note: All specifications are subject to change.

