

W1

APPLY TO

INCLINED ROOSETOP

W1 color steel tile photovoltaic roof bracket system

5-45°


- 1. The wind resistance ability, the structure of the professional design makes more convenient installation process.
- 2. Install the parts less, fast installation, cost-effective.
- 3. The structure design of high density to ensure the least amount of container space.
- 4. Strict quality control to ensure the service life of the stents.

Installation PLAllocation	color steel tile roof
Installation Angle	5-45°
Wind load	36km/s
Snow load	16KN/m ²
Apply panel type	Frame or no frame
Panels arrangement standard	The vertical or horizontal AS/NZS1170 DIN 1055 JIS C 8956:2011 Intemational Building Code IBC 2009 California Building Cod e CBC 2010
The material	AL6005-T5(Yang level surface oxidation)、 8.8 hot zinc impregnation
Fasteners	SUS304
Spare parts color	Aluminum alloy Natural white or color according to customer's requirements
quality assurance	10 years



30% ↑ 0.03K/s
↓ 0.2K/s

01



external member

02



End clamp external member

03



Angle Flyback external member

04



Rail

05



Inside hexagon socket head bolt & nut external membe

Tianjin Coldbend Imp. & Exp. Co., Ltd

08

WWW.TUCOLDBEND.COM

Tianjin Coldbend Imp. & Exp. Co., Ltd

07

WWW.TUCOLDBEND.COM