

■ VRLA (Valve Regulated Lead Acid Battery) ESG 120 (2V, 120AH/10hr)

► Applications

- UPS System
- Communication Equipments
- Renewable Energy(Solar & Wind power)
- Medical Equipments
- Computer Back-up Power
- Security & Alarm Systems
- Power Plants
- Railroad Traffic Signals
- FA Systems

► Technical Features

- Excellent energy-saving capacity combined with high reliability
- Maintenance - Free (No topping up during whole service life)
- Leakproof (Adopted sealed structure)
- Safety Valve for increased reliability against gas generation
- Very low gassing due to the internal gas recombination
- Minimized Self-Discharge
- Excellent recovery following the deep discharge
- 10 years design life at 25 °C ambient temperature
- Self discharge rate: < 2.5% per month at 77°F (25 °C)
- Container & Cover : Acid-resistant ABS resin
Option : UL94-V0 = ABS
- Completely recyclable

※ The AGM battery does not require equalizing charge.

► Specifications

Nominal Capacity (AH)	• 120
Nominal Voltage (V)	• 2
Dimensions (L*W*H*TH) (mm)	• 115*166*198*230
Weight (kg)	• 10.0
Design life (at 25 °C)	• 10 years
Internal Resistance (mΩ)	• 0.5
Self Discharge (at 25 °C)	• 2.5% / Month
Operating Temperature Range (°C)	• -15 ~ +50
Charge voltage (at 25 °C)	• 2.22V



► Discharge Table in Amperes

Final Voltage	10min	15min	20min	30min	40min	50min	1h	2h	3h	5h	8h	10h
1.8V / Cell	154	126	105	87	73	64	58.9	38.0	28.5	17.5	12.2	11.4
1.7V / Cell	190	162	141	112	87	76	68	39	29	18	12.5	11.6
1.6V / Cell	211	183	156	115	95	86	76	40	28	19	12.5	11.6

