

PRODUCT



SOLARWATT Panel vision H 3.0 pure

Glass-Glass module

Solid quality with high performance

Thanks to their modern design Solarwatt glass-glass modules deliver the highest long-term yields. They are robust and more resilient than their predecessors. PERC half-cut-cells enable modules that are optimized for maximum performance.

The solar cells are embedded almost indestructibly in the glass-glass composite and thus optimally protected against all weather effects and mechanical stress. Solarwatt can therefore offer a 30-year warranty on performance and product quality.

The Solarwatt FullCoverage insurance is included for 5 years and free of charge. It insures almost all risks and takes effect even if the modules do not produce electricity or deliver less than expected in the event of damage.



PRODUCT QUALITY

- ammonia resistant
- intensive hailstorm resistant
- salt mist resistant
- LeTID tested
- 100 % plus-sorting
- PID protected
- snow-load warranty

SERVICE

FullCoverage insurance
included (up to 1,000 kWp*)

Simple returns policy
as per „Delivery terms for Solarwatt solar modules“


30 Year Product Warranty
as per „Warranty conditions for Solarwatt solar modules“

30 Year Performance Warranty
on 87 % of nominal power as per „Warranty conditions for Solarwatt solar modules“

* country-specific deviations apply



DIMENSIONS



GENERAL DATA

Module technology	Glass-glass laminate; aluminum frame
Covering material	Tempered solar glass with anti-reflective finish, 2mm
Encapsulation	Solar cells in polymer encapsulation, white
Backing material	Tempered glass, 2 mm
Solar cells	120 monocrystalline high power PERC-solar cells
Cell dimensions	166 x 83 mm
L x W x H / Weight	1,780 ^{±2} x 1,052 ^{±2} x 40 ^{±0,3} mm / appr. 25 kg
Connection technology	Cables 2 x 1,2 m/ 4 mm ² Stäubli Electrical MC4 connectors
Bypass diodes	3
Max. system voltage	1,000 V
IP rating	IP67
Protection class	II (acc. to IEC 61140)
Fire class	A (acc. to IEC 61730/UL 790) E (acc. to EN 13501-1) B _{ROOF} (t1) (acc. to EN13501-5)
Certified mechanical ratings as per IEC 61215	Suction load up to 3,600 Pa (test load 5,400 Pa) Pressure load up to 8,100 Pa (test load 12,150 Pa)
Recommended stress load as per Installation Instructions	Please refer to the specifications in the Installation Instructions and Warranty Conditions.
Qualifications	IEC 61215 IEC 61730 LeTID IEC 61701 IEC 62804 IEC 62716 MCS 005

ELECTRICAL DATA (STC)

STC (Standard Test Conditions): Irradiation intensity 1,000 W/m², spectral distribution AM 1,5 | Temperature 25 ± 2 °C, in accordance to EN 60904-3

Nominal power P _{max}	365 Wp	370 Wp	375 Wp
Nominal voltage V _{mp}	34.5 V	34.6 V	34.7 V
Nominal current I _{mp}	10.7 A	10.8 A	10.9 A
Open circuit voltage V _{oc}	41.2 V	41.3 V	41.4 V
Short circuit current I _{sc}	11.2 A	11.3 A	11.4 A
Module efficiency	19.6 %	19.9 %	20.2 %

Measurement tolerances: P_{max} ±5 %; V_{oc} ±10 %; I_{sc} ±10 %, I_{mp} ±10 %

Reverse-current power rating I_s: 20 A, operating modules with an external power source is only permissible if using a phase fuse with a tripping current of ≤ 20 A.

ELECTRICAL DATA (NMOT AND WEAK LIGHT)

NMOT (Nominal Module Operating Temperature): Irradiation intensity 800 W/m², spectral distribution AM 1,5, Temperature 20 °C
Weak light conditions: Irradiation intensity 200 W/m², Temperature 25 °C, Wind speed 1 m/s, load operation

Nominal power P _{max} @NMOT	271 W	275 W	279 W
Nominal power P _{max} @200 W/m ²	71,4 W	72,4 W	73,3 W

Measurement tolerances: P_{max} ±5 %; V_{oc} ±10 %; I_{sc} ±10 %, I_{mp} ±10 %


Reduction of module efficiency when irradiance is reduced from 1,000 W/m² to 200 W/m² (at 25 °C): 4 ± 2 % (relative) / -0,6 ± 0,3 % (absolute).

THERMAL FEATURES

Operating temperature range	-40 ... +85 °C
Ambient temperature range	-40 ... +45 °C
Temperature coefficient P _{max}	-0.37 %/K
Temperature coefficient V _{oc}	-0.27 %/K
Temperature coefficient I _{sc}	0.04 %/K
NMOT	44 °C

CHARACTERISTIC LINES (PERFORMANCE CLASS 375 WP)

Voltage characteristic line at different temperatures and irradiances



TRANSPORT AND PACKAGING

Modules per pallet	32
Pallet dimensions (gross) L x W x H	1,800 x 1,070 x 1,550 mm
Gross weight per pallet	847 kg
Pallets per truck	14
Modules per truck	448