


# SP150M-36

High Efficiency Monocrystalline PV Module

Electrical Data	SP150M-36
Maximum power (Pmax)	150W
Voltage at Pmax (Vmp)	18.30V
Current at Pmax (Imp)	8.20A
Open-circuit voltage (Voc)	22.80V
Short-circuit current (Isc)	8.78A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/ °C
Temperature coefficient of power	-(0.5±0.05)%/ °C
NOCT (Air 20°C; Sun 0.8kW/m <sup>2</sup> wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	1000V DC
Power tolerance	+ 3%

\* STC: Irradiance 1000W/m<sup>2</sup>, AM1.5 spectrum, module temperature 25°C

\* NOCT: Nominal operating cell temperature (the data is only for reference)




**25** 25-year guarantee  
for 80% rated power

**10** 10-year product  
workmanship warranty

**10** 10-year guarantee  
for 90% rated power

## Dimensions Of PV Module



\*All Dimensions in mm

Specifications	SP150M-36
Cells	Mono 156.75x156.75 mm
No. of cells and connections	36(4x9)
Module dimension	1482x676x35 mm 58.35x26.61x1.38 inch
Weight	11.5 kg
No. of Mounting Holes	8
No. of Waterspout Holes	16

## Features

- Excellent power generation performance
- Nominal 12V DC for standard output.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.

## Applications

- Traffic & Safety
- Federal Government
- Agricultural
- Security
- Telecommunications
- Water and Wastewater
- Weather & Environmental Monitoring
- RV Camper
- Emergency Power
- Telemetry

## Characteristics

