

# Sunlife Solar www.sunlifesolar.com.pk

36 CELLS SLS095P

SLS100P


POLYCRYSTALLINE SLS115P SLS120P

# **PHYSICAL CHARACTERISTICS**

Model NO.	SLS095P	SLS100P
Peak power(Pmax)	95W	100W
Maximum power voltage(Vmp)	17.8V	18V
Maximum power current(Imp)	5.33A	5.56A
Short-circuit current(Isc)	5.65A	5.89A
Open circuit voltage(Voc)	22.1V	22.4V
Cell efficiency(η)	16.80%	17.20%
Power tolerance:	±3%	
	40004 .0500	

Operating temperature -40°C to +85°C

Maximum system voltage 715VDC




# TEMPERATURE COEFFICIENT

**ELECTRICAL SPECIFICATIONS** 

Current temperature coefficient 0.037%/ $^{\circ}$ C Voltage temperature coefficient -0.34%/ $^{\circ}$ C Power temperature coefficient -0.48%/ $^{\circ}$ C

STC: Irradiance of 1000W /m2, AM 1.5, Cell Temperature of 25°C

#### **ELECTRICAL CHARACTERISTICS**



#### **MECHANICAL SPECIFICATIONS**

Cell Type 156mm x 156mm

Number of Cells 36 cells in series

Weight 8.7 kg (19.14 lbs)

Dimension 1000×670×30mm

Max Load 5400 Pascals (112 lb/ft2)

Junction Box

## **ELECTRICAL SPECIFICATIONS**


Cable/Connector


Model NO.	SLS115P	SLS120P
Peak power(Pmax)	115W	120W
Maximum power voltage(Vmp)	17.8V	18V
Maximum power current(Imp)	6.46A	6.67A
Short-circuit current(Isc)	6.84A	7.06A
Open circuit voltage(Voc)	22.1V	22.4V
Cell efficiency(η)	16.80%	17.20%
Power tolerance:	±3%	

Operating temperature -40°C to +85°C

Maximum system voltage 715VDC

## PHYSICAL CHARACTERISTICS





#### **TEMPERATURE COEFFICIENTS**

Current temperature coefficient	0.037%/℃	
Voltage temperature coefficient	-0.34%/℃	
Power temperature coefficient	-0.48%/℃	
STC: Irradiance of 1000W /m2, AM 1.5, Cell Temperature of 25°C		

#### MECHANICAL SPECIFICATIONS

MECHANICAL SPECIFICATIONS		
Cell Type	156mm x 156mm	
Number of Cells	36 cells in series	
Weight	10.3 kg (22.66bs)	
Dimension	1185×670×30mm	
Max Load	5400 Pascals ( 112 lb/ft2)	
Junction Box		

Cable/Connector

# ELECTRICAL CHARACTERISTICS

