


Deutsche
Qualität
Garantiert

TIER 1
BloombergNEF



AESOLAR

since 2003



AURORA

HIGH ENERGY YIELD RELIABILITY DURABILITY

30
years

Performance
Guarantee

15
years

Product
Guarantee

530W-550W

AE ME-110BD Series

MONO-CRYSTALLINE PV MODULES
HALF-CUT CELLS • BIFACIAL • DOUBLE-GLASS

www.ae-solar.com

110

HALF
CELLS

210
mm

CELL
SIZE



LID
RESISTANT



PID
RESISTANT



SALT CORROSION
RESISTANT



SAND
RESISTANT



AMMONIA
RESISTANT




HIGHLY STABLE
AND TOUGH



IEC 61215
IEC 61730
Regular Production Surveillance
Type Tested and Monitored

IEC 62716 (Ammonia corrosion)
IEC 61701 (Salt mist corrosion)
IEC 60068 (Sand and dust)
IEC 62804 (PID resistance)




AE ME-110BD Series 530W-550W



MONO-CRYSTALLINE PV MODULES
HALF-CUT CELLS • BIFACIAL • DOUBLE-GLASS

Mechanical and design specification

Cell type	Gallium-doped Mono c-Si PERC, Half-cut cells, 210 mm
No. of cells	110
Bifaciality	70±5%
Glass	2.0 mm, high transmission, AR coated, tempered
Encapsulation	EVA
Back cover	2.0 mm, high transmission solar glass, tempered
Junction box	IP68 rated, 3 Bypass Diodes
Frame	30 mm anodized Aluminium alloy
Cable	1 x 4 mm ² , 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	2383 mm x 1095 mm x 30 mm
Weight	32 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa/ 244 kg/ m ²
Mechanical load	5400 Pa/ 550 kg/ m ²






Packaging information

Packaging configuration	36 pcs / pallet
Loading capacity	720 pcs / 40 HQ
Size / Pallet	1130 mm x 1140 mm x 2500 mm (upright)
Weight	1185 kg / pallet

Temperature ratings

Operating temperature	(°C)	-40 to +85
Temp. coefficient of P _{max}	(%/°C)	-0.34
Temp. coefficient of V _{oc}	(%/°C)	-0.25
Temp. coefficient of I _{sc}	(%/°C)	0.04
Nom. operating temp. NOCT	(°C)	43 ± 2



Electrical specifications (STC*): AE530ME-110BD AE535ME-110BD AE540ME-110BD AE545ME-110BD AE550ME-110BD

Parameter	Symbol	AE530ME-110BD	AE535ME-110BD	AE540ME-110BD	AE545ME-110BD	AE550ME-110BD
Nominal Max. Power	P _{max} (Wp)	530	535	540	545	550
Maximum operating voltage	V _{MPP} (V)	30.8	31.0	31.2	31.4	31.6
Maximum operating current	I _{MPP} (A)	17.21	17.28	17.33	17.37	17.4
Open-circuit voltage	V _{oc} (V)	37.1	37.3	37.5	37.7	37.9
Short-circuit current	I _{sc} (A)	18.31	18.36	18.41	18.47	18.52
Module efficiency	η (%)	20.31	20.50	20.69	20.89	21.08
Power tolerance	(W)	0~+5				
Maximum system Voltage	(V)	1500				
Maximum series fuse rating	(A)	30				

*STC: Standard test conditions (Irradiance 1000 W/m², Cell temperature 25°C and air mass of AM1.5)

Electrical specifications (NMOT*): AE530ME-110BD AE535ME-110BD AE540ME-110BD AE545ME-110BD AE550ME-110BD

Parameter	Symbol	AE530ME-110BD	AE535ME-110BD	AE540ME-110BD	AE545ME-110BD	AE550ME-110BD
Nominal Max. Power	P _{max} (Wp)	401	405	409	413	417
Maximum operating voltage	V _{MPP} (V)	28.6	28.8	29.0	29.2	29.3
Maximum operating current	I _{MPP} (A)	14.02	14.06	14.10	14.15	14.19
Open-circuit voltage	V _{oc} (V)	34.9	35.1	35.3	35.5	35.7
Short-circuit current	I _{sc} (A)	14.73	14.8	14.84	14.88	14.92

*NMOT: Normal Module Operating Temperature (Irradiance 800 W/m², Ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.

