

SERIES **N5**

610-630W Mono

156 Half-Cell Layout
M10/182mm N-TOPCon Cell



N-TOPCon Cell Technology



Half Cut Cell Technology



SMBB Technology



Excellent Anti-PID Low LID Performance




Less Hot Spot Shading Effects



Higher Power Output Lower BOS & LCOE

Linear performance Warranty



Comprehensive Certificates

- ISO9001:2015 QMS
- ISO14001:2015 EMS
- ISO45001:2018 OHSMS
- IEC61215/IEC61730 Standard Quality
- IEC61701/IEC62716 Salt/Mist/Ammonia Tests



SUNLIKE SOLAR CO., LTD.

Add: No. 509 Datong Road, Wuxi, Jiangsu, China


T: +86 510 8899 0686; Email: solar@sunlikesolar.com

www.sunlikesolar.com

Mono I 610 - 630W

MECHANICAL CHARACTERISTICS

Solar Cells	N-type Mono
No. of Cells	156 (6x26)
Dimensions	2465 x 1134 x 35mm
Weight	30.0kg
Front Glass	3.2mm coated tempered glass
Frame	Anodized aluminium alloy
Junction Box	Ip68 rated (3 by pass diodes)
	4.0mm ²
Output Cables	300mm (+) / 300mm (-)
	Length can be customized
Connectors	Mc4 compatible
Mechanical load test	5400Pa



ELECTRICAL PARAMETERS

POWER CLASS	LNVH-610N		LNVH-615N		LNVH-620N		LNVH-625N		LNVH-630N	
	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT	STC	NMOT
Maximum power (Pmax)	610W	459W	615W	463W	620W	467W	625W	471W	630W	475W
Open Circuit Voltage (Voc)	54.99V	52.50V	55.18V	52.66V	55.37V	52.82V	55.56V	52.98V	55.74V	53.13V
Short Circuit Current (Isc)	14.22A	11.41A	14.28A	11.47A	14.34A	11.53A	14.40A	11.59A	14.46A	11.65A
Voltage at Maximum power (Vmpp)	45.52V	42.34V	45.69V	42.48V	45.86V	42.61V	46.02V	42.74V	46.19V	42.87V
Current Maximum Power (Impp)	13.40A	10.84A	13.46A	10.90A	13.52A	10.96A	13.58A	11.02A	13.64A	11.08A
MODULE EFFICIENCY (%)	21.82%		22.00%		22.18%		22.36%		22.54%	



STC: Irradiance 1000W/m², cell temperature 25°C, AM1.5G NMOT: Irradiance 800W/m², ambient temperature 20°C, wind speed 1m/s, AM1.5G

PACKING CONFIGURATION

Container	20'GP	40'HQ
Pieces per pallet	31	31
Pallets per container	4	16
Pieces per container	124	496

I-V CURVE

LNVH-620N/I-V



OPERATING CHARACTERISTICS

Operating Module Temperature	-40°C to +85°C
Maximum System Voltage	1500 DC (IEC)
Maximum Series Fuse Rating	25A
Power Tolerance	0/+5W

TEMPERATURE CHARACTERISTICS

Nominal Operating Temperature (NMOT)	45±2°C
Temperature Coefficient of Pmax	-0.29%/°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Isc	+0.045%/°C

Note: The specifications, data and technical characteristics provided in this data sheet are subject to changes due to continuous R&D, product innovation and improvement. SUNLIKE SOLAR reserves the right to modify the information any time without prior notice.