



PCO 100-136kW

Three Phase On-Grid Solar Inverter

-  9-12 MPP Trackers
-  150% DC Input Oversizing
-  Smart I-V Curve Diagnosis Supported
-  DC & AC Type II SPD
-  Intelligent Fault Detection
-  IP66 Protection
-  AFCI
-  PID
-  SVG
- AFCI Function (Optional)
- PID Recovery Function (Optional)
- Night SVG Function (Optional)

	PCO100KTR	PCO100KTR-F	PCO110KTR	PCO110KTR-F	PCO136KTR-L	PCO136KTR-LF	PCO136KTR-X	PCO136KTR-XF
Input (DC)								
Max. Input Power	150kW						160kW	
Max. Input Voltage		1100V						
Start Voltage			250V					
Rated Input Voltage	620V			730V			780V	
Full-load MPP Voltage Range	530V ~ 850V						560V ~ 850V	
MPP Voltage Range		180V ~ 1000V						
Number of MPP Trackers / String per MPPT	9 / 2		10 / 2				12 / 2	
Max. Current per MPPT	26A	30A	26A	30A	26A	30A	26A	30A
Max. Short Circuit Current per MPPT						40A		
Output (AC)								
Max. Output Current	158.8A		174.6A				160.4A	
Rated Output Power	100kW		110kW				136kW	
Max. Output Power	110kVA		121kVA				150kVA	
Rated Grid Frequency	50Hz / 60Hz							
Rated Grid Voltage	230Vac / 400Vac, 3L / N / PE, 3L / PE		277Vac / 480Vac, 3L / N / PE, 3L / PE		311Vac / 540Vac, 3L / N / PE, 3L / PE			
Power Factor			>0.99 (0.8 leading~0.8 lagging)					
THDi						<3% (Rated Power)		
Efficiency								
Max. Efficiency			98.70%					
European Efficiency			98.50%					
MPPT Efficiency			99.90%					
Protection								
DC reverse polarity protection							Yes	
Anti-islanding protection							Yes	
AC short circuit protection							Yes	
Residual current monitoring unit							Yes	
Insulation resistance monitoring							Yes	
Ground fault monitoring							Yes	
Grid monitoring							Yes	
PV string monitoring							Yes	
Surge protection							Type II	
AFCI protection							Optional	
PID recovery function							Optional	
SVG function							Optional	
Communication								
Display			LED / LCD / Bluetooth+App					
Communication			Standard: RS485 / USB Optional: WiFi / DRM / Bluetooth					
Standard Compliance								
Grid Connection Standards			IEC 61727, IEC 62116, IEC 60068, IEC 61683, VDE-AR-N 4110:2018, VDE-AR-N 4105:2018, VDE-AR-N 4120:2018, EN 50549, AS/NZS 4777.2:2015, CEI-021, VDE 0126-1-1/A1 VFR 2014, UTE C15-712-1:2013, DEWA DRRG, NRS 097-2-1, MEA/PEA, C10/11, G98/G99, CEI-016					
Safety / EMC			IEC 62109-1:2010, IEC 62109-2:2011, EN 61000-6-2:2005, EN 61000-6-3:2007/A1:2011					
General Data								
Dimensions (W x H x D)			1050 x 660 x 330 mm					
Weight	95kg	98kg	101kg					
Operating Temperature Range		-30° C ~ +60° C						
Cooling Method		Smart Cooling						
Protection Degree		IP66						
Max. Operating Altitude		4000m						
Relative Humidity		0 ~ 100%						
Topology		Transformerless						
Night Power Consumption		<1W						
Warranty		5 years (Standard) / 10 years (Optional)						