




Technical Data

Parameter	600W	800W	1000W
Maximum Power	600W	800W	1000W
Rated Power	600W	800W	1000W
Maximum DC Voltage	60V	60V	60V
Maximum DC Current	10A	13.3A	16.7A
Maximum AC Voltage	230V	230V	230V
Maximum AC Current	2.7A	3.6A	4.5A
Efficiency	97.5%	97.5%	97.5%
Temperature Range	-25°C to 55°C	-25°C to 55°C	-25°C to 55°C
Dimensions (mm)	100x100x40	100x100x40	100x100x40
Weight (kg)	0.1	0.1	0.1

Product System Application



- R** Support reactive power compensation
 - M** 100% protection design, 10 years warranty
 - M** 1 MPP tracker, module level monitoring
 - W** IFC, ZigBee or WiFi communication
 - C** Rapid shutdown function
-



Technical Data

Parameter	600W	800W	1000W
Maximum Power	600W	800W	1000W
Rated Power	600W	800W	1000W
Maximum DC Voltage	60V	60V	60V
Maximum DC Current	10A	13.3A	16.7A
Maximum AC Voltage	230V	230V	230V
Maximum AC Current	2.7A	3.6A	4.5A
Efficiency	97.5%	97.5%	97.5%
Temperature Range	-25°C to 55°C	-25°C to 55°C	-25°C to 55°C
Dimensions (mm)	100x100x40	100x100x40	100x100x40
Weight (kg)	0.1	0.1	0.1

