

# LD Mark III series solar inverters

# autarco

The Autarco LD series Mark III inverters offer the latest in grid tied inverter technology. The inverter is a key element in a solar PV power plant and these inverters provide the reliable basis for Autarco's unique kWh guarantee.



Eligible for Autarco's insured kWh Guarantee



Reduced Fire Risk due to Integrated AFCI



Extremely lightweight and silent



Wide MPP tracker range



Waterproof IP66 enclosure



## QUALITY CERTIFICATES


- ◆ EN 50549-1, EN 61000-6-1/3 (CE), IEC 62109-1/2
- ◆ VDE 4105, VDE 0126, C10/11, NTS 631, RD 1699, RD 413




## GENERAL CHARACTERISTICS

<b>Dimensions (W x H x D)</b>	310 x 563 x 219mm
<b>Net weight</b>	17.8kg
<b>Mounting</b>	Wall bracket
<b>Max. site altitude</b>	4000m
<b>IP protection class</b>	IP66
<b>Isolation type</b>	Transformerless
<b>Cooling principle</b>	Natural convection
<b>Noise level, typically</b>	< 20dBA
<b>Product guarantee</b>	5 year standard (10 & 15 year optional)
<b>Consumption monitoring</b>	Optional with meter
<b>Communication interfaces</b>	1 x RS485
<b>Monitoring Options</b>	WiFi, GPRS, 5G and Ethernet
<b>DC switch</b>	Integrated (optionally excluded)
<b>Power Export Limitation</b>	Integrated


Front




Side



Bottom



Bracket



# INPUT CHARACTERISTICS

	S2.LD3000-MIII	S2.LD4000-MIII	S2.LD5000-MIII	S2.LD6000-MIII	S2.LD8000-MIII	S2.LD9000-MIII	S2.LD10000-MIII
Max. DC voltage (V)	1100	1100	1100	1100	1100	1100	1100
Max. PV input power (W)	4500	6000	7500	9000	12000	13500	15000
MPP tracker voltage range (V)	160-1000	160-1000	160-1000	160-1000	160-1000	160-1000	160-1000
Start-up DC voltage (V)	180	180	180	180	180	180	180
Number of MPP trackers	2	2	2	2	2	2	2
Max. DC current per MPPT (A)	16	16	16	16	16	16	16
Max. short circuit current (A)	25	25	25	25	25	25	2
DC connections per MPPT	1	1	1	1	1	1	1
DC connection type	MC4	MC4	MC4	MC4	MC4	MC4	MC4
Turn on power (W)	10	10	10	10	10	10	10

# OUTPUT CHARACTERISTICS

AC connection	Plug-in	Plug-in	Plug-in	Plug-in	Plug-in	Plug-in	Plug-in
Power connection	3-phase	3-phase	3-phase	3-phase	3-phase	3-phase	3-phase
Rated AC power (W)	3000	4000	5000	6000	8000	9000	10000
Max. AC power (W)	3300	4400	5500	6600	8800	9900	11000
Rated Grid Voltage (V)	3P/N/PE, 220 V / 380 V, 230 V / 400 V						
Rated Grid Frequency (Hz)	50 Hz / 60 Hz						
Rated AC current (A)	4.6 / 4.3	6.1 / 5.8	7.6 / 7.2	9.1 / 8.7	12.2 / 11.5	13.7 / 13.0	15.2 / 14.4
Max. AC current (A)	4.7	6.4	7.9	9.5	12.7	14.3	15.9
Power factor	0.8...1...0.8	0.8...1...0.8	0.8...1...0.8	0.8...1...0.8	0.8...1...0.8	0.8...1...0.8	0.8...1...0.8
Harmonic distortion (%)	< 2	< 2	< 2	< 2	< 2	< 2	< 2
Night-time power consumption (W)	< 1	< 1	< 1	< 1	< 1	< 1	< 1
Standby power consumption (W)	6	6	6	6	6	6	6

# EFFICIENCY

Max. efficiency	98.30 ~ 98.7%
EU efficiency	97.7 ~ 98.10%
MPPT efficiency	> 99.50%

# OTHER CHARACTERISTICS

Operating temperature range	-25°C to +60°C
Relative humidity range	0% to 100%

# PROTECTION

DC overvoltage protection	Integrated
DC reverse polarity protection	Integrated
Short circuit protection	Integrated
Grid monitoring	Integrated
Residual current detection	Integrated
Insulation resistance monitoring	Integrated
Temperature protection	Integrated
Islanding protection	Integrated
Arc-fault circuit interrupter	Integrated

The specifications contained in this datasheet may deviate slightly from our actual products due to on-going product improvement and are subject to change at any time without prior notice.

