

JONSOL

JSGM144


535-545W

MONO

(BiF)



The high quality and reliability of JONSOL are based on many years of production and industry experience, a mature module design and the automatic production process. The result is guaranteed high-performance JONSOL modules.



*Linear performance guarantee

The monocrystalline JONSOL module of the Half Cell Series consists of 144 half cells. It delivers high power ratings and higher levels of efficiency and is therefore particularly suitable for limited areas and roof installations. The partial shading yield is increased thanks to the half cells.

JONSOL quality features JSGM144 182 (BiF)


- Module efficiency up to 21.03 percent
- Monocrystalline high-performance solar cells
- Structured special glass
- Fully automatic production lines
- Certification according to IEC 61215, EN IEC 61730
- Comprehensive quality controls
- 100 % electroluminescence test
- IP67 junction box for safety and long-term weather resistance
- Plus sorting up to 3 percent for a higher yield at the same price

JONSOL


JSGM144

535-545W


MONO (BiF)



1000 W/m² 600 W/m² 200 W/m²
800 W/m² 400 W/m²



Modules
per pallet:
31 pcs.



Pallets // modules
per container:
20 pcs. // 620 pcs.

Technical data

	STC	NMOT	STC	NMOT	STC	NMOT
Nominal power (P _{max})	535 W	402 W	540 W	406 W	545 W	409 W
Nominal voltage (V _{mp})	41.45	38.59	41.61	38.74	41.77	38.89
Nominal current (I _{mp})	12.91	10.41	12.98	10.47	13.05	10.53
Open circuit voltage (V _{oc})	49.31	46.41	49.46	46.55	49.61	46.69
Short-circuit current (I _{sc})	13.79	11.12	13.86	11.18	13.93	11.23
Efficiency	20.65 %		20.84 %		21.03 %	
Permitted operating temperature	-40°C - +85°C					
Maximum system voltage	1500 V					
Protection class	II					
Fire Safety Class (UL)	A					
Reverse Current Capability (I _R)	30 A					
Power tolerance (W)	0 - +3 %					

Measurement tolerances P_{mp} ± 3 %, I_{sc} & U_{oc} ± 3 % at STC: 1000 W/m², 25 ± 2 °C, AM 1.5 according to IEC 60904-3 // NMOT: 800 W/m², AM 1.5

Rear side power gain (BiF only)

Maximum Power (P _{max})	5 %	562 W	567 W	572 W
Module Efficiency STC (%)	5 %	21.68 %	21.88 %	22.08 %
Maximum Power (P _{max})	15 %	615 W	621 W	627 W
Module Efficiency STC (%)	15 %	23.74 %	23.97 %	24.19 %
Maximum Power (P _{max})	25 %	669 W	675 W	681 W
Module Efficiency STC (%)	25 %	25.81 %	26.05 %	26.29 %

Temperature coefficient (STC)

Temperature coefficient (P _{max})	-0.36 %/K
Temperature coefficient (V _{oc})	-0.29 %/K
Temperature coefficient (I _{sc})	0.048 %/K

Standard temperature at normal operating conditions (NOCT) 42 +/-3°C

Mechanical data

Cell Type	monocrystalline, 144 half cells 182 x 91 mm
Module size (L x B x H)	2285 x 1134 x 35 mm
Weight	32.5 kg
Front cover	Solar glass 2 mm, tempered, AR coated
Back cover	Solar glass 2 mm, tempered, AR coated
Frame	anodized aluminum alloy
Junction Box	IP68, 3 diodes
Cable	4 mm ² , ≥ 1.2 m, IP68
Connector	MC4 or comparable to MC4, IP68
max. mechanical load	Tensile load: 2400 Pa, Pressure load: 5400 Pa

Version 2/2023. The specifications and properties contained in this data sheet may vary slightly and are not guaranteed. JONSOL reserves the right to make changes to the information contained herein at any time without notice due to continuous innovation, research and product improvement. Please always keep the current version of the data sheet available. It is a binding part of the contract for all contractual partners when purchasing and selling the products described in the data sheets. The instructions of the manual must be followed. The data sheet corresponds to DIN EN 50380.