

TS5000 (LiFePO₄ 51.2V100Ah, 5120.0Wh)

- Safety in use
- Low self discharge rate
- Good high temperature performance High
- Cycle times and long service life
- High energy density and conversion efficiency Environmental
- Friendly, without any heavy metals Easy installation, easy BMS
- modbus protocol can communicate with the inverter



	Item	Specification
Electrical Characteristics	Nominal Voltage	51.2V
	Nominal Capacity	100Ah
	Energy	5120Wh
	Internal Resistance	≤20mΩ
	Cycle Life	>3000 Cycles
	Months Self Discharge	<3%
	Efficiency of Charge	100% @0.2C
	Efficiency of Discharge	96~99% @1C
Standard Charge	Charge Voltage	58.4 ± 0.2V
	Charge Mode	0.2C to 58.4V, then 58.4V, charge current 0.02C(CC/CV)
	Charger Current	50A
	Max. Charge Current	75A
	Charge Cut-off Voltage	59.2V ± 0.2V
Standard Discharge	Continuous Current	50A
	Max. Pulse Current	100A
	Discharge Cut-off Voltage	40V
Environmental	Charge Temperature	0°C to 45°C (32F to 113F) @60±25% Relative Humidity
	Discharge Temperature	-20°C to 60°C (-4F to 140F) @60± 25% Relative Humidity
	Storage Temperature	0°C to 40°C (32F to 104F) @60± 25% Relative Humidity
	Water Dust Resistance	IP30
Mechanical	Cell & Method	3.2V50AH-16S2P
	Plastic Case	4U standard case
	Dimensions (in./mm.)	482*400*177MM
	Weight (lbs./kg.)	43Kg
	Terminal	100A through terminal
	Protocol (optional)	RS485/RS232CAN
	BMS	16S100A

Product Design

BMS



LiFePO₄ Cell Package



LiFePO₄ in Box



SHEN ZHEN TAICO TECHNOLOGY CO., LTD

- Add: 2F Building 6, Langkou Industrial Park, Longhua New District, Shenzhen China 518000
- Tel: 86-755-29822748 Fax: 86-755-29822462
- E-mail: info@taicopower.com
- Website: www.taicopower.com