



Grade A LiFePO₄ Cell

RELIABLE

Compatible with Major PCS Brand

♦ CALABLE

Scalable from 5 to 30 kWh



Model	AIR 4900-3U	AIR 5220-3U
	7 1000 00	7 1 0220 00

	Performance	
Nominal Voltage	48 Vdc	51.2 Vdc
Nominal Capacity	102 Ah	102 Ah
Battery Energy	4.9 kWh	5.2 kWh
CUS	4.4 kWh	4.7 kWh
Charge Current	50 A	50 A
Charge Power	2400 W	2560 W
Discharge Current	100 A	100 A
Discharge Power	4800 W	5120 W
Short circuit current	350	0 A

Communication	
Display	SOC status indicator, LED indicator
Communication	CAN, RS485, RS232

General Specification		
Dimension (WxDxH mm)	440 x 500 x 132mm	
Weight (kg)	41 kg	43 kg
Installation	Rack mounted or wall mounted	
Working Temperature	-20°C-60°C	
Operating / Storage	≤95%	RH
Max Operating Altitude	≤200	00 m
IP Rating	IP2	20
Cell Technology	LiFePO4, Lithium	Iron Phosphate
Cycle life	6000 Cycles @ 80% DoD	/ 25℃ / 0.5C _, 60% EOL
Scalability	Max 6 batterie	es in parallel

Standard Compliance (more available upon request)			
Certificates		CE, UN38.3	

Ordering and Deliverable Part	
Product ordering part	AIR 4900/5220-3U Battery (Cable / wall mount included)