



SpolarPV
Easy Invest, More Returns



21.53 %

Module efficiency

430 W

Highest power output



Product warranty



Linear power warranty

SPV430-PM6-132

405-430Watt



High Efficiency

Higher power conversion efficiency benefited from advanced Passivated Emitter and Rear Cell (PERC) technology.



Anti-reflection

Less than 20% reflectivity with minimum glare.



Low-light Performance

Certified to withstand: wind load (2400 Pa), snow load (5400 Pa) and hail strike.




Severe Weather Resilience

Advanced glass and cell surface texture designs ensure excellent performance in low environment.



Durability against extreme environmental conditions

High salt mist resistance certified by IEC 61701, suitable for coastal areas.



■ Linear performance warranty ■ Standard performance warranty



ISO9001:2016 ISO14001:2016
OHSAS18001:2011 certified factory.
IEC61215 IEC61730 certified products.

Electrical Characteristics at Standard Test Conditions (STC)

Module Type	SPV405-PM6-132	SPV410-PM6-132	SPV415-PM6-132	SPV420-PM6-132	SPV425-PM6-132	SPV430-PM6-132
Maximum Power - Pmax (W)	405	410	415	420	425	430
Maximum Power Voltage - Vmp (V)	36.78	36.92	37.05	37.18	37.41	37.69
Maximum Power Current - Imp (A)	11.01	11.11	11.20	11.30	11.36	11.41
Open-circuit Voltage - Voc (V)	44.48	44.64	44.80	44.96	45.12	45.28
Short-circuit Current - Isc (A)	11.60	11.70	11.80	11.90	11.98	12.07
Module Efficiency STC (%)	20.34 %	20.52 %	20.84 %	21.03 %	21.28 %	21.53 %


Electrical Characteristics at Normal Operating Cell Temperature (NOCT)

Module Type	SPV405-PM6-132	SPV410-PM6-132	SPV415-PM6-132	SPV420-PM6-132	SPV425-PM6-132	SPV430-PM6-132
Maximum Power - Pmax (W)	305	310	313	317	320	324
Maximum Power Voltage - Vmp (V)	34.86	34.98	35.11	35.15	35.36	35.69
Maximum Power Current - Imp (A)	8.75	8.86	8.91	9.02	9.05	9.08
Open-circuit Voltage - Voc (V)	41.90	42.05	42.20	42.35	42.46	42.61
Short-circuit Current - Isc (A)	9.46	9.58	9.64	9.75	9.78	9.81
Power Tolerance	0 ~ +3W		Operating Temperature (°C)		-40 °C ~ +85 °C	
Temperature Coefficients of Pmax	-0.35% / °C		Maximum System Voltage		1500 V	
Temperature Coefficients of Voc	-0.275% / °C		Maximum Series Fuse Rating		25 A	
Temperature Coefficients of Isc	0.045% / °C		Nominal Operating Cell Temperature		45 ± 2 °C	



Mechanical Characteristics

Cell Type	Mono-crystalline PERC 166x83 mm
No. of Cells	132 (6x22)
Dimensions	1924x1038x30 mm
Weight	21.0 kg
Glass	3.2mm, High Transmission, Low Iron, Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP68, MC4 Compatible, 3 Bypass Diode
Output Cables	1x4.0 mm ² , Length: 300 mm or Customized Length
Packaging Configuration	72pcs/stack,864pcs/40'HQContainer (Two pallets=One stack)

Current-Voltage Curve under different irradiance



Current-Voltage Curve under different working temperatures



www.spolarpv.com