



## Pure Sine Wave Inverter ASR-12200/24200/48200/60200



### PRODUCT CHARACTERISTICS

With multi-functional LCD display and good safety performance, including overtemperature protection, input overvoltage protection, input low voltage protection, output overload protection, output short circuit protection, when Input reverse polarity occurs the blown fuse.

High conversion efficiency and start fast, surface surface powder coating treatment, good friction resistance, and can resist a certain external force of extrusion or collision;

With strong load adaptability and stability.

Wide Temperature Range • High Safety • Pure Sine Wave • Flexible Expansion

### Features and Advantages



**Wide Temperature Range**  
Range of -5 to 40 °C



**Pure Sine Wave**  
Power 2000W



**Expandable**  
Higher Capacity available



**High Safety**  
With functional protection



**Cooling Fan**  
Instant heat dissipation



**Easy to operate**  
Save time and effort

# Technical Parameters

|   |  |            |
|---|--|------------|
| Model   | Pure sine wave inverter<br>ASR-12200/24200/48200/60200 |            |
| <b>OutPut</b>   |  |            |
| Nominal Output Power  | 2000W  |            |
| Max Power   | 2200W  |            |
| Peak Power  | 4400W  |            |
| AC Output Voltage Accuracy  | ±10V   |            |
| AC Output Current(220V)   | 9.1A   |            |
| WaveForm  | pure sine wave   |            |
| Output Frequency  | 50Hz/60Hz  |            |
| Nominal output Voltage  | 110V/240V  |            |
| AC Output Over Current(220V)  | 12V  | ≥10        |
|   | 24V  | ≥10        |
|   | 48V  | ≥10        |
|   | 60V  | ≥10        |
| Max Effciency   | 12V  | 85%        |
|   | 24V  | 90%        |
|   | 48V  | 90%        |
|   | 60V  | 90%        |
| <b>InPut</b>  |  |            |
| Voltage Range   | 12V  | 10-15V     |
|   | 24V  | 20-30V     |
|   | 48V  | 40-60V     |
|   | 60V  | 50-75V     |
| DC Input Current  | 12V  | 191.6A     |
|   | 24V  | 91.6A      |
|   | 48V  | 45.8A      |
|   | 60V  | 36.6A      |
| No load Current Draws   | 12V  | <0.5A      |
|   | 24V  | <0.3A      |
|   | 48V  | <0.12A     |
|   | 60V  | <0.12A     |
| Power Consumption   | 12V  | ≤6W        |
|   | 24V  | ≤5W        |
|   | 48V  | ≤5W        |
|   | 60V  | ≤5W        |
| <b>Protection Function</b>  |  |            |
| Input reverse polarity protection/Input reverse connection protection | integrated/blown fuse                                  |            |
| Short Circuit Protection  | integrated//blown fuse                                 |            |
| power protection  | ≥2300W   |            |
| over temperature  | integrated ( cooling fin 85°C )                        |            |
| malfunction alert   | buzzer integrated                                      |            |
| over voltage protection   | 12V  | 15V ± 0.3V |
|   | 24V  | 30V ± 0.3V |
|   | 48V  | 60V ± 0.3V |
|   | 60V  | 75V ± 0.3V |
| low voltage protection  | 12V  | 10V ± 0.3V |
|   | 24V  | 20V ± 0.3V |
|   | 48V  | 40V ± 0.3V |
|   | 60V  | 50V ± 0.3V |

| Automatic Recovery               |  |              |
|----------------------------------|--|--------------|
| over voltage                     | 12V  | 14V ±0.5V    |
|                                  | 24V  | 28V ± 0.5V   |
|                                  | 48V  | 56V ± 0.5V   |
|                                  | 60V  | 70V ± 0.5V   |
| low voltage                      | 12V  | 12.6V ± 0.5V |
|                                  | 24V  | 25.2V ± 0.5V |
|                                  | 48V  | 50.4V ± 0.5V |
|                                  | 60V  | 63V ± 0.5V   |
| Display&Interface                |  |              |
| LCD Display                      | input voltage/output voltage/frequency/power   |              |
| LCD Display the malfunction code | overvoltage(F1)<br>Lowvoltage(F2)<br>overheat(F3)<br>overload(F4)<br>Short Circuit(F5) |              |
| USB Port                         | Type-C; QC3.0; 5V2.1A  |              |
| General Date                     |  |              |
| Operating Temperature Range      | -5°C-40°C  |              |
| Relative Humidity                | 0~90%  |              |
| Size (L*W*H )                    | 390*180*93MM   |              |
| Weight                           | 3.85kgs  |              |