





**∜AFE** 

Grade A LiFePO4 Cell RELIABLE

Compatible with Major PCS Brand

**♦** CALABLE

Scalable from 15.5 to 232.5 kWh



| Model | AIR 15K5 |
|-------|----------|
|       |          |

|                       | Performance |
|-----------------------|-------------|
| Nominal Voltage       | 51.2 Vdc    |
| Nominal Capacity      | 304 Ah      |
| Battery Energy        | 15.5 kWh    |
| CUS                   | 14.0 kWh    |
| Charge Current        | 150 A       |
| Charge Power          | 7680 W      |
| Discharge Current     | 200 A       |
| Discharge Power       | 10240 W     |
| Short circuit current | 540 A       |

| Communication |  |  |
|---------------|--|--|
| Display       | SOC status indicator, LED indicator, LCD Display |  |
| Communication | CAN, RS485, RS232                                |  |

| General Specification  |   |  |
|------------------------|---|--|
| Dimension (WxDxH mm)   | 500 x 230 x 780 mm                            |  |
| Weight (kg)            | 120 kg  |  |
| Installation           | Floor Stand or Wall Mount                     |  |
| Working Temperature    | -20°C-60°C                                    |  |
| Operating / Storage    | ≤95% RH                                       |  |
| Max Operating Altitude | ≤2000 m                                       |  |
| IP Rating              | IP20  |  |
| Cell Technology        | LiFePO <sub>4</sub> , Lithium Iron Phosphate  |  |
| Cycle life             | 6000 Cycles @ 80% DoD / 25°C / 0.5°C, 60% EOL |  |
| Scalability            | Max 15 batteries in parallel                  |  |

| Standard Compliance (more available upon request) |  |            |
|---|--|------------|
| Certificates                                      |  | CE, UN38.3 |

| Ordering and Deliverable Part |  |  |
|-------------------------------|--|--|
| Product ordering part         | AIR 15K5 Battery (Cable / wall mount included) |  |