



Solar roof curve tile (CIGS)

Class A. Fire-proof
Class F. Wind-proof
Exquisite craft with High quality



Ultra light

Ultrathin

Super strong

Efficient conversion rate

Thin-film technology subversion and innovation

Cold resistance, tide resistance, wind resistance, impact resistance and other characteristics to adapt to the vast majority of the construction



PHYSICAL PARAMETERS

Product Model	HW-MQSB-V2
Color	Black
Specification	721 (length) *500 (width) *33 (arch height) mm
Weight	6.5kg
Connector	MC4
Warranty	25 years

ELECTRICAL PERFORMANCE PARAMETERS

Chip type	copper, indium, gallium and selenium
Open-circuit voltage	10.6V
Power	30W (Standard Edition)
PMPP Current	3.5A
Short circuit current	4.0A
PMPP time voltage	8.6V

PERFORMANCE LEVEL

Load rating	5400pa
Waterproof grade	IP67
Fire rating	A
Hail resistance level	Level 4 (ANSI FM 4473)
Working temperature	-40°C~+85°C
Operating humidity	0~80%

The overall product warranty is 10 years, and the power guarantee by the 25th year, the power generation shall not be less than 85% of the nominal power

Beijing Shan Hu International Technology Co., Ltd
Address: Room 130, Apartment 1, 1st floor, Building 31, Nanhai Jiayuan Liuli, Yinghai Town, Daxing District, Beijing
Email: sales.manager@sangsolar.com
<https://www.sangsolar.com>