


THIP Series

120-CELL ONE-THIRD CUT MONOCRYSTALLINE SOLAR MODULE

SAXXX-DE21M(10)
385-410Watt



Key Feature



Mould efficiency up to 21.3% achieved through advanced cell technology and manufacturing process



Qualified encapsulating materials and stringent production process control ensure the product is highly PID resistant



Lower LCOE, Reduced BOS cost, higher return on investment



Special cutting and soldering technology leads low hotspot risk



Ideal choice for Large-scale Power station installation



Certified to withstand: wind load (2400Pa) and snow load(5400Pa)


Certifications and standards:
IEC 61215, IEC 61730, conformity to CE



JidiSolar Delivers Reliable Performance Over Time

- Lead manufacturer of crystalline silicon photovoltaic modules
- Automatic production line and world-class technology
- Long-term reliability tests
- 2 EL inspection ensuring defect-free solar modules
- Rigorous quality control to meet the international quality standard: ISO9001;ISO18001 and ISO45001


Linear Performance Warranty



10 Years Product Warranty 25 Years Linear Power Warranty

Special Cell Design

The unique cell design leads to reduced electrodes resistance and raised cells efficiency. Residual stress reduction can be more even, reducing the micro-cracks and hotspot risks



MBB

IP68 Rated Junction Box



The IP68 rated junction box ensures an outstanding waterproof level, supports installations in all orientations and reduces stress on the cables, high reliable performance, low resistance connectors ensure maximum output for the highest energy production

THIP Series

120-CELL ONE-THIRD CUT MONOCRYSTALLINE SOLAR MODULE

SAXXX-DE21M(10) 385-410Watt

Electrical Data(STC)

Maximum Power	Pmax(W)	385	390	395	400	405	410
Maximum Power Voltage	Vmp(V)	33.8	34.0	34.2	34.4	34.6	34.8
Maximum Power Current	Imp(A)	11.40	11.48	11.55	11.63	11.71	11.79
Open Circuit Voltage	Voc(V)	40.7	40.9	41.1	41.3	41.5	41.7
Short Circuit Current	Isc(A)	12.09	12.17	12.25	12.33	12.35	12.43
Module Efficiency	(%)	20.0	20.3	20.5	20.8	21.1	21.3
Output Power Tolerance	(W)	0~+5					

STC: 1000W/m² Irradiation, 25°C Module Temperature and AM 1.5g Spectrum

Electrical Data(NOCT)

Maximum Power	Pmax(W)	292	296	300	304	308	312
Maximum Power Voltage	Vmp(V)	31.6	31.8	32.0	32.2	32.4	32.6
Maximum Power Current	Imp(A)	9.24	9.31	9.38	9.44	9.51	9.57
Open Circuit Voltage	Voc(V)	38.2	38.4	38.6	38.8	39.0	39.2
Short Circuit Current	Isc(A)	9.81	9.88	9.95	10.01	10.08	10.14

NOCT: 800W/m² Irradiation, 20°C Ambient Temperature and Wind Speed 1m/s

Mechanical Characteristics

Number of Cells	120(10x12)
Dimension LxWxH(mm)	1754x1096x35 (69.06x43.15x1.38 inch)
Weight(kg)	21.0(46.3lb)
Front Glass	3.2mm High Transmission, Coated Tempered Glass
Back-sheet	White
Frame	Silver White, Anodized Aluminum Alloy
Junction Box	IP68 Rated
Cable	TUV, 1x4mm ² ; Anode: 300mm, Cathode: 300mm
Number of Diodes	3
Wind/Snow Load	2400Pa/5400Pa
Connectors	MC Compatible

For more details please check the installation manual

Temperature Ratings

Nominal Operating Cell Temperature(NOCT)	44±2°C
Temperature Coefficient of Isc	+0.05%/°C
Temperature Coefficient of Voc	-0.30%/°C
Temperature Coefficient of Pmax	-0.39%/°C

Maximum Ratings

Operating Temperature	-40 to +85°C
Maximum System Voltage	1500V DC
Maximum Series Fuse Rating	20A

Packing Configuration

Module per Pallet	31PCS
Module per Stack	62PCS
Module per Container(20feet)	186PCS
Module per Container(40feet)	936PCS


Optional

Connectors	<input type="checkbox"/> Original MC
Cable Length	<input type="checkbox"/> 1400mm
Frame	<input type="checkbox"/> Black
Back-sheet	<input type="checkbox"/> Black


Contact us for More Information

website: www.sangsolar.com email: sales.manager@sangsolar.com


Module Dimension




Back View



I-V Curve at Different Irradiation (400W)



P-V Curve at Different Irradiation (400W)



Noting: READ THE INSTALLATION MANUAL BEFORE USING THE PRODUCT