

PiE AIR superLIGHT FOLD 200+

200 Watt 18 V BLK/TRNS



SUPER LIGHT

GLASS-FREE AND FRAMELESS, NEVERTHELESS ROBUST SOLAR MODULE DUE TO ETFE WITH A NET WEIGHT OF 4.60 KG



EASY TO FIT & FOLDABLE

16 LONG HOLES FOR EASY AND UNIVERSAL USAGE



HIGH PERFORMANCE

USAGE OF SPECIAL HALF-CUT MONOCRYSTALLINE SOLAR CELLS TO ABSORB THE MAXIMUM OF SUNLIGHT AND CONVERT INTO ENERGY





WARRANTY

6 YEARS PRODUCT WARRANTY

25 YEARS LINEAR PERFORMANCE WARRANTY (81% POWER ASSURANCE)

Type	PiE AIR superLIGHT FOLD 200+
Maximum Power (Pmax)	200 W+
Maximum Power Voltage (Vmp)	18.00 V
Maximum Power Current (Imp)	11.10 A
Open Circuit Voltage (Voc)	22 V±3 %*
Short Circuit Current (Isc)	11.7 A±3 %*
Power temperature coefficient	- 0.045%/°C
Voltage temperature coefficient	- 0.33%/°C
Current temperature coefficient	- 0.05%/°C
Power Selection	1~5 W
Maximum System Voltage	IEC 1500 V
Module Efficiency (%)	> 19,4 %
Certification	CE – RoHS





SIZE: 1010 x 1050 x 4.5

