



Safe and reliable

High safety LiFePO4 battery. Designed to comply with IEC, UL standards.



Long Life

8,000+ cycles 10-year standard warranty with extended option up to 15 years



Easy Installation& Expansion

Integrated design, wall or floor mounted.Support multiple packs in parallel



Higher adaptability

-20°C-55°C support Wide temperature range cell built inside,make you enjoy the sunsine freely The AS-HD series are high-voltage batteries, built in advanced smart battery management system and Tier 1 ATL's ultra safe LiFePO4 cells, designed specially for Germany, the US, Australia, the UK, and other mainstream residential PV storage markets, perfect for PV systems, especially the residential one.

Technical Datasheet

		AS-6HD	AS-10HD	AS-13HD	AS-16HD	AS-20HD
		Specification				
Nominal energy (kWh)		6.68	10.03	13.37	16.71	20.06
Nominal Voltage(V)		204	307	409	512	614
Working voltage range (V)		185~227	278~340	371~454	464~568	556~681
Max. Charging Current(A)		32 (15°C~45°C)				
Max. Discharging current(A)		32(0°C~45°C)				
Operating temperature range		- 20°C~55°C				
Recommended operating temperature		15°C~30°C				
Storage conditions	Temperatur	-20°C ~ + 45°C				
	Humidity	5%-95%RH				
Cycle Life		8000 Cycles				
Dimensions		793*276*850	793*276*1100	793*276*1350	793*276*1600	793*276*1850
Weight(kg)		84	117.5	151	184.5	218
Ingress protection		IP65				
Operation altitude		≤2000m				
Communication		CAN,RS485				
Module Series connection		25	3S	4S	5S	6S
Rack Parallel connection		4P				
Certification		IEC62619:2022/CE/VDE 2510-50/UL1973/UL9540A/UN38.3+PI965				

21 22