

EVO 5N

565-585W SE5-72HBDN-type TOPCon
Bifacial Dual Glass Solar Module**22.65%**

Max. Module Efficiency

10-30% Additional Power Generation

30 years lifespan brings 10-30% additional power generation comparing with conventional P-type module.

ZERO LID (Light Induced Degradation)

N-type solar cell has no LID naturally which can increase power generation.

Higher Reliability

Adopted SunEvo latest S-TOPCo 2.0 technology, No polysilicon wrap around, Full electrical isolation, Zero leakage current; Much Safer for roof.

Better Weak Illumination Response

Higher power output even under low-light environments like on cloudy or foggy days.

Better Temperature Coefficient

Higher power generation under working conditions, thanks to passivating contact cell technology.


Quality Management System and Product Certification

IEC61215/61730, IEC62804(PID), IEC61701(Salt),
IEC62716 (Ammonia), IEC60068-2-68(Sand),
ISO 9001:2015/quality management system,
ISO 14001:2015/environmental management system,
ISO 45001:2018/occupation health safety management system,
ISO 50001:2011/energy management system,
IEC TS 62941-2016/PV industry quality management system.


Quality Guarantee

25 year Materials Warranty


30 year Power Warranty



Drawings



Product Image



Mechanical Characteristics

Solar Cells	N-type Mono
No. of Cells	144 (6×24)
Dimensions	2279 x 1134 x 30mm
Weight	31.5kg
Glass	Front: 2.0mm coated semi-tempered glass; Back: 2.0mm semi-tempered glass
Frame	Anodized aluminium alloy
Junction Box	Ip68 rated (3 by pass diodes)
Output Cables	4mm ² , 300mm (+) / 300mm (-), Length can be customized
Connectors	MC4 compatible
Mechanical Load Test	5400Pa
Packaging	36pcs/box, 180pcs/20'GP, 720pcs/40'HQ

Operating Characteristics

Operating Module Temperature	-40°C to +85°C
Maximum System Voltage	1500V DC (IEC)
Maximum Series Fuse Rating	30A
Power Tolerance	0~+5W



Temperature Characteristics

Nominal Operating Temperature (NMOT)	45±2°C
Temperature Coefficient of Pmax	-0.29%/°C
Temperature Coefficient of Voc	-0.25%/°C
Temperature Coefficient of Isc	+0.045%/°C

Electrical Parameters (STC*)

Module Type: SE5-72HBD	565	570	575	580	585
Maximum Power (Pmax/W)	565	570	575	580	585
Voltage at Maximum Power (Vmpp/V)	43.43	43.58	43.73	43.88	44.02
Current at Maximum Power (Impp/A)	13.01	13.08	13.15	13.22	13.29
Open Circuit Voltage (Voc/V)	51.90	52.10	52.30	52.50	52.70
Short Circuit Current (Isc/A)	13.77	13.83	13.89	13.95	14.01
Module Efficiency (%)	21.86	22.07	22.26	22.45	22.65

I-V Curve



Bifacial Output (Rearside Power Gain)

		565	570	575	580	585
5%	Maximum Power (Pmax/W)	593	599	604	609	614
	Module Efficiency STC (%)	22.96	23.16	23.36	23.56	23.77
15%	Maximum Power (Pmax/W)	650	656	661	667	673
	Module Efficiency STC (%)	25.14	25.36	25.59	25.81	26.03
25%	Maximum Power (Pmax/W)	706	713	719	725	731
	Module Efficiency STC (%)	27.33	27.57	27.81	28.05	28.29

1. Standard Test Conditions [STC]: irradiance 1000W/m², AM 1.5, ambient temperature 25°C according to EN 60904-3;
 2. Tolerance of Pm: 0~+5W, Measuring uncertainty of power: ±3%. Performance deviation of Voc [V], Isc [A], Vm [V] and Im [A]: ±3%.