



PVX-6720T, 2V

PVX-2240T, 6V

PVX-2580L, 12V

Nominal Capacity Ampere Hours @ 25° C (77° F) to 1.75 volts per cell

Sun Xtender® Part Number	Volt	Industry Reference	Overall Dimensions Inches (mm)			Unit Weight LB / KG	1 Hour Rate	2 Hour Rate	4 Hour Rate	8 Hour Rate	24 Hour Rate	100 Hour Rate
			Length	Width	Height							
PVX-340T	12	U1	7.71 (196)	5.18 (132)	6.89 (175)	25/11.4	21	27	28	30	34	37
PVX-420T	12	U1 Tall	7.71 (196)	5.18 (132)	8.05 (204)	30/13.6	26	33	34	36	42	44
PVX-490T	12	22NF	8.99 (228)	5.45 (138)	8.72 (221)	36/16.4	31	39	40	43	49	54
PVX-560T	12	22NF	8.99 (228)	5.45 (138)	8.72 (221)	40/18.2	36	45	46	49	56	62
PVX-690T	12	24	10.22 (260)	6.60 (168)	8.75 (222)	51/23.2	42	53	55	60	69	78
PVX-840T	12	24	10.22 (260)	6.60 (168)	8.75 (222)	57/25.9	52	66	68	74	84	96
PVX-890T	12	31	12.93 (328)	6.75 (172)	8.79 (223)	62/28.2	55	70	72	79	89	100
PVX-1040T	12	27	12.01 (305)	6.60 (168)	8.75 (222)	63/28.6	65	82	85	93	104	118
PVX-1080T	12	31	12.93 (328)	6.75 (172)	8.79 (223)	65/29.5	68	86	88	97	108	124
PVX-1180T	12	31	12.93 (328)	6.75 (171)	8.79 (223)	72/32.7	72	92	95	104	118	135
PVX-1290T	12	31	12.93 (328)	6.75 (171)	8.79 (223)	75/34	79	100	103	113	129	146
PVX-1530T	12	30H Tall	13.46 (342)	6.77 (172)	11.77 (299)	91/41.3	95	120	124	136	153	176
PVX-2120L	12	4D	20.76 (527)	8.70 (221)	9.77 (248)	127/57.6	136	172	176	194	212	250
PVX-2580L	12	8D	20.76 (527)	10.89 (277)	9.77 (248)	159/72.1	165	209	214	236	258	300
PVX-1030T	6	24	10.21 (259)	6.60 (168)	8.92 (227)	42/19.1	65	82	85	93	103	118
PVX-1380T	6	24	10.21 (259)	6.60 (168)	8.92 (227)	51/23.2	84	106	110	120	138	155
PVX-2240T	6	GC2	10.28 (261)	7.06 (179)	9.92 (252)	67/30.4	143	180	185	204	224	260
PVX-2560T	6	31	12.90 (328)	6.75 (171)	8.96 (228)	75/34	158	200	206	226	256	292
PVX-3050T	6	GC2 Tall	10.28 (261)	7.06 (179)	12.94 (329)	91/41.3	190	245	270	280	305	354
PVX-4050HT	6	L-16	11.64 (296)	6.95 (177)	15.73 (399)	120/54.4	266	345	360	376	405	443
PVX-5340T ¹	2	31	12.90 (328)	6.75 (171)	8.96 (228)	64/29.0	330	420	432	474	534	604
PVX-6480T ¹	2	31	12.90 (328)	6.75 (171)	8.96 (228)	67/30.5	408	516	528	582	648	746
PVX-6720T ¹	2	GC2	10.28 (261)	7.06 (179)	9.92 (252)	70/31.8	429	540	555	612	672	780
PVX-7680T ¹	2	31	12.90 (328)	6.75 (171)	8.96 (228)	75/34	474	600	618	678	768	876
PVX-9150T ¹	2	GC2 Tall	10.28 (261)	7.06 (179)	12.94 (329)	94/42.6	570	735	810	840	915	1062
PVX-12150HT ¹	2	L-16	11.64 (296)	6.95 (177)	15.73 (399)	124/56.2	798	1035	1080	1128	1215	1329

¹ 4 terminal battery

For full specifications, refer to our website, www.sunxtender.com

Specifications subject to change without notice. Never install batteries in an airtight or sealed enclosure. Insure installation is adequately ventilated.

The item or technical data contained herein has been reviewed and approved for general release on the basis that it contains no export-controlled information.

