

Model	SPT-2500	SPT-3000	SPT-3500	SPT-4000	SPT-5000	SPT-6000	SPT-7000	SPT-8000	SPT-10000	
Input	DC Voltage									
	24V or 48V(Optional)									
	Voltage Range									
	21-33VDC or 42-63VDC									
	No Load Current	<25W	<30W	<35W	<40W	<50W	<60W	<70W	<80W	<100W
Draw										
Efficiency	92%									
DC Connector	Cables									
Output	AC Voltage									
	120V	240V	120V	240V	120V	240V	120V	240V	120V	240V
	120V	240V	1500W	3000W	1750W	3500W	2000W	4000W	2500W	5000W
	3000W	6000W	3500W	7000W	4500W	9000W	5000W	10000W	6000W	12000W
	Regulation	±0.1% or ±0.1% (Optional)								
Waveform	Pure Sine Wave									
AC Regulation	±3%									
Protection	Low Voltage Alarm									
	19.5-21.5v /43-45v									
	Low Voltage Shut Down									
	19.5-20.5v / 41.5-42.5v									
	Over Load									
	Shut Off Output									
	Over Voltage Shut Down									
30.5v /61.5v										
Over Thermal										
Shut Off Output Automatically										
Fuses										
Short Circuit										
Environment	Working Temperature									
	Between - 10C and +50C									
	Working Humidity									
20% - 91% RH non-condensing										
Storage Temperature										
Between - 30 C and + 70 C										
Others	Start									
	Soft Start									
	Cooling Ways									
Cooling Fan										
Total Harmonic Distortion										
THD < 5%										
Pack	Machine size									
	14.9" x 8.4" x 5.3inch				21" x 9.8" x 5.3inch				21" x 8.8" x 5.3inch	
	Net Weight(kg)				18.9KG				17KG	
Packaging Type										
Carton Package										