



Deutsche
Qualität
Garantiert

AURORA
P-TYPE PERC TECHNOLOGY

ME-132BS 640W-660W

High in energy yield, reliability and durability

21.27%
MAXIMUM EFFICIENCY


132
HALF CELLS

30 YEARS Performance Warranty up to **30 YEARS*** Product Warranty

*The regular product warranty is 15 years, please refer to the latest version of AESOLAR Limited Warranty for the duration of the product warranty under special conditions. for extensions, please contact AESOLAR staff.



OUR PERFORMANCE WARRANTY



SYSTEM AND PRODUCT CERTIFICATIONS



IEC 61215 IEC 61730
Regular Production Surveillance
www.tuv.com
ID 1111251295

IEC 62716 (Ammonia corrosion)
IEC 61701 (Salt mist corrosion)
IEC 60068 (Sand and dust)
IEC 62804 (PID resistance)




www.ae-solar.com

AE ME-132BS 640W-660W

P-TYPE PERC TECHNOLOGY PV MODULE

BIFACIAL • SINGLE-GLASS



Electrical specifications (STC*):

Parameter	Symbol	640	645	650	655	660
Nominal max. power	P_{max} (Wp)	640	645	650	655	660
Maximum operating voltage	V_{MPP} (V)	37.00	37.20	37.40	37.60	37.80
Maximum operating current	I_{MPP} (A)	17.30	17.34	17.38	17.42	17.46
Open-circuit voltage	V_{oc} (V)	45.10	45.30	45.50	45.70	45.90
Short-circuit current	I_{sc} (A)	18.19	18.25	18.32	18.38	18.43
Module efficiency	η (%)	20.63	20.79	20.95	21.11	21.27
Power tolerance	(W)				0~+5	
Maximum system voltage	(V)				1500	
Maximum series fuse rating	(A)				35	

*STC: Standard Test Conditions (irradiance 1000 W/m², cell temperature 25°C and air mass of AM1.5), measurement tolerance P_{max} : ±3%

Electrical specifications (NMOT*):

Parameter	Symbol	480	484	488	492	496
Nominal max. power	P_{max} (Wp)	480	484	488	492	496
Maximum operating voltage	V_{MPP} (V)	34.70	34.90	35.10	35.30	35.50
Maximum operating current	I_{MPP} (A)	13.84	13.87	13.90	13.94	13.97
Open-circuit voltage	V_{oc} (V)	42.00	42.20	42.40	42.60	42.80
Short-circuit current	I_{sc} (A)	14.19	14.60	14.66	14.70	14.74

*NMOT: Normal Module Operating Temperature (irradiance 800 W/m², ambient temperature 20°C, air mass of AM1.5 and wind speed of 1 m/s)

Mechanical and design specification

Cell type	Gallium-doped mono c-Si PERC, half-cut cells
No. of cells	132
Bifaciality	70 ± 5%
Front cover	3.2 mm glass, high transmission, AR coated, tempered
Encapsulation	EVA
Back cover	Transparent backsheet
Junction box	IP68 rated, 3 bypass diodes
Frame	30 mm anodized aluminium alloy
Cable (including Connector)	1 x 4 mm ² , 350 mm length or customized
Connectors	MC 4 / MC 4 compatible
Dimension	2383 mm x 1302 mm x 30 mm
Weight	31.5 kg
Hail resistance	Max. Ø 25 mm at 23 m/s
Wind load	2400 Pa or 244 kg/m ²
Snow load	5400 Pa or 550 kg/m ²

Temperature ratings

Operating temperature	-40 to +85°C
Temp. coefficient of P_{max}	-0.34 %/°C
Temp. coefficient of V_{oc}	-0.25 %/°C
Temp. coefficient of I_{sc}	0.040 %/°C
Nom. operating cell temp. NOCT	43 ± 2°C

Packaging information

Packaging configuration	36 pcs / pallet
Loading capacity	648 pcs / 40 HQ
Size / Pallet	1350 mm x 1140 mm x 2500 mm (Upright)
Weight	1167 kg / pallet

The specifications and characteristics contained in this datasheet may deviate slightly from our actual products due to the product developments and uncertainty of measurement devices. The specifications included in the datasheet are subject to change without prior notice.